2-881545-2 ACTIVE

AMPMODU | Modu Connector System

TE Internal #: 2-881545-2

Novo, Open Top, 2 Position, 2.54 mm [.1 in] Centerline, Signal, -65

– 105 °C [-85 – 221 °F], Modu Connector System, Board-to-Board

Jumpers & Shunts

View on TE.com >



Connectors > PCB Connectors > Board-to-Board Connectors > Board-to-Board Jumpers & Shunts











Shunt Type: Novo

Shunt Style: Open Top Number of Positions: 2

Centerline (Pitch): 2.54 mm [.1 in] Contact Current Rating (Max): 3 A

Contact Mating Area Plating Material

Contact Base Material

Features

Product Type Features

Product Type Features	
Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	2
Electrical Characteristics	
Termination Resistance	15 mΩ
Body Features	
Handle	With
Primary Product Color	Red
Contact Features	
Contact Mating Area Plating Material Thickness	.762 μm[30 μin]

Gold

Phosphor Bronze



Shunt Type	Novo
Shunt Style	Open Top
Contact Current Rating (Max)	3 A
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Thermoplastic
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Product Height	10.9 mm[.429 in]
Usage Conditions	
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Jumper & Shunt Packaging	Loose Piece
Packaging Quantity	14000
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not reviewed for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts








Also in the Series | Modu Connector System



Automotive Connector Caps & Covers (3)



Board-to-Board Jumpers & Shunts(5)



Connector Caps & Covers(1)



Connector Hardware(4)



Customers Also Bought



















Documents

Product Drawings

AMP SHUNT LOW PROFI

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_2-881545-2_K.2d_dxf.zip

English

Customer View Model

ENG_CVM_2-881545-2_K.3d_igs.zip

English

Customer View Model

ENG_CVM_2-881545-2_K.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Agency Approvals

Agency Approval Document

English