

https://www.phoenixcontact.com/us/products/1415777



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYPORT B6 panel mounting base, with single locking latch, with plastic protective cover, with stainless steel front plate connections, 1x D-SUB 9 (female/terminal block)

Your advantages

• Good shielding in the event of electromagnetic interference

Commercial data

Item number	1415777
Packing unit	1 pc
Sales key	BF69
Product key	BF7EGX
GTIN	4055626805788
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	22.22 g
Country of origin	US



https://www.phoenixcontact.com/us/products/1415777



Technical data

Product properties

Product type	Stackable housing set
Housing type	Panel mounting base
Application	Standard
Туре	B6
Protective cover	yes

Electrical properties

Rated voltage (III/3)	60 V ()
Rated current	5 A ()

Connection data

Tightening torque	1.5 2 Nm

Dimensions

Width 53 mm Height 30.5 mm Length 80.5 mm Drill hole distance, horizontal 70 mm Drill hole distance, vertical 32 mm Hole diameter 4.5 mm Installation dimensions Width of the assembly cutout 35 mm Length of the assembly cutout 52 mm	Dimensional drawing	98 1 94.5 PAGE NICE 9
Length 80.5 mm Drill hole distance, horizontal 70 mm Drill hole distance, vertical 32 mm Hole diameter 4.5 mm Installation dimensions Width of the assembly cutout 35 mm	Width	53 mm
Drill hole distance, horizontal 70 mm Drill hole distance, vertical 32 mm Hole diameter 4.5 mm Installation dimensions Width of the assembly cutout 35 mm	Height	30.5 mm
Drill hole distance, vertical 32 mm Hole diameter 4.5 mm Installation dimensions Width of the assembly cutout 35 mm	Length	80.5 mm
Hole diameter 4.5 mm Installation dimensions Width of the assembly cutout 35 mm	Drill hole distance, horizontal	70 mm
Installation dimensions Width of the assembly cutout 35 mm	Drill hole distance, vertical	32 mm
Width of the assembly cutout 35 mm	Hole diameter	4.5 mm
	Installation dimensions	
Length of the assembly cutout 52 mm	Width of the assembly cutout	35 mm
Longin of the assembly edicut	Length of the assembly cutout	52 mm

Material specifications

Seal material	NBR, conductive
	NBR, conductive
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Material, protective cover	PA
Locking latch material	Polyamide

Connector

Contact insert design	with 1x D-SUB 9 pin/Terminal block slot locking #4-40 UNC bolts
-----------------------	---

Environmental and real-life conditions



https://www.phoenixcontact.com/us/products/1415777



Ambient conditions

Degree of protection	IP66
	IP67
Impact strength	IK08
Ambient temperature (operation)	-40 °C 125 °C (Housing)


1415777

https://www.phoenixcontact.com/us/products/1415777




Drawings

Dimensional drawing



Dimensional drawing

Dimensional drawing



Mounting cutout



https://www.phoenixcontact.com/us/products/1415777



Classifications

ECLASS

ECLASS-11.0	27440101
ECLASS-12.0	27440113
ECLASS-13.0	27440113

1415777

https://www.phoenixcontact.com/us/products/1415777



Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



https://www.phoenixcontact.com/us/products/1415777



Accessories

C-SCFFI 2,5/6,3X0,8 - Connector

3240547

https://www.phoenixcontact.com/us/products/3240547



Slip-on sleeve, fully isolated, blue, 1.5 ... 2.5 mm², for plug 6.3 x 0.8 mm

C-SCFFI 6/6,3X0,8 - Connector

3240541

https://www.phoenixcontact.com/us/products/3240541



Slip-on sleeve, fully insulated, yellow, 4 ... 6 mm², for 6.3 x 0.8 mm plugs



https://www.phoenixcontact.com/us/products/1415777



C-SCFFI 1,5/6,3X0,8 - Connector

3240538

https://www.phoenixcontact.com/us/products/3240538



Slip-on sleeve, fully isolated, red, 0.5 ... 1.5 mm^2 , for plug 6.3 x 0.8 mm

C-SCFFI 2,5/4,8X0,8 - Connector

3240540

https://www.phoenixcontact.com/us/products/3240540



Slip-on sleeve, fully isolated, blue, 1.5 ... 2.5 mm², for plug 4.8 x 0.8 mm



https://www.phoenixcontact.com/us/products/1415777



C-SCFFI 2,5/4,8X0,5 - Connector

3240539

https://www.phoenixcontact.com/us/products/3240539



Slip-on sleeve, fully isolated, blue, 1.5 ... 2.5 $\mbox{mm}^2,$ for plug 4.8 x 0.5 \mbox{mm}

C-SCFFI 1,5/4,8X0,8 - Connector

3240537

https://www.phoenixcontact.com/us/products/3240537



Slip-on sleeve, fully isolated, red, 0.5 \dots 1.5 mm², for plug 4.8 x 0.8 mm



https://www.phoenixcontact.com/us/products/1415777



C-SCFFI 1,5/4,8X0,5 - Connector

3240536

https://www.phoenixcontact.com/us/products/3240536



Slip-on sleeve, fully isolated, red, 0.5 ... 1.5 mm², for plug 4.8 x 0.5 mm

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com