



GEO Full DimensionsMale Connector
24° Flareless / ISO 6149**GE-R-ED** Full DimensionsMale Connector
24° Flareless / BSPP

DIN 3852-2 Form E

TUBE FITTING PART #	END SIZE		I 1 (mm)	S1 (mm)	STANDARD Pressure Rating (bar)				
	1 (mm)	2 Metric Thread			EO		EO-2		
					A3C	71	MS	A3C	71
GEO04LLM	4	M8 x 1	9.5	11	100			100	
GEO04LLM10x1	4	M10 x 1	9.5	13	100			100	
GEO06LLM	6	M10 x 1	8.0	13					
GEO06LM	6	M10 x 1	8.5	14	315			315	
GEO08LM	8	M12 x 1.5	10.0	17	315			315	
GEO10LM	10	M14 x 1.5	11.0	19	315			315	
GEO12LM	12	M16 x 1.5	12.5	22	315			315	
GEO15LM	15	M18 x 1.5	13.5	24	315			315	
GEO18LM	18	M22 x 1.5	14.5	27	315			315	
GEO22LM27x2	22	M27 x 2	16.5	32	160			160	
GEO28LM	28	M33 x 2	17.5	41	160			160	
GEO35LM	35	M42 x 2	17.5	50	160			160	
GEO42LM	42	M48 x 2	19.0	55	160			160	
GEO06SM	6	M12 x 1.5	13.0	17	630			630	
GEO08SM	8	M14 x 1.5	15.0	19	630			630	
GEO10SM	10	M16 x 1.5	15.0	22	630			630	
GEO12SM	12	M18 x 1.5	17.0	24	630			630	
GEO16SM	16	M22 x 1.5	18.5	27	400			400	
GEO20SM	20	M27 x 2	20.5	32	400			400	
GEO25SM	25	M33 x 2	23.0	41	400			400	
GEO30SM	30	M42 x 2	23.5	50	400			400	
GEO38SM	38	M48 x 2	26.0	55	315			315	

For EO-2 part number, insert "Z" between size and pressure series.
Example: GEO06ZLMA3C

TUBE FITTING PART #	END SIZE		I 1 (mm)	S1 (mm)	STANDARD Pressure Rating (bar)				
	1 (mm)	2 BSPP			EO		EO-2		
					A3C	71	MS	A3C	71
GE04LLRED	4	G 1/8 A	9.5	14	100			100	
GE06LLRED	6	G 1/8 A	8.0	14	100			100	
GE06LRED	6	G 1/8 A	8.5	14	315	315		315	315
GE06LR1/4ED	6	G 1/4 A	10.0	19	315	315		315	315
GE08LR1/8ED	8	G 1/8 A	9.5	14	315	315		315	315
GE08LRED	8	G 1/4 A	10.0	19	315	315		315	315
GE08LR3/8ED	8	G 3/8 A	11.5	22	315	315		315	315
GE10LRED	10	G 1/4 A	11.0	19	315	315		315	315
GE10LR3/8ED	10	G 3/8 A	12.5	22	315	315		315	315
GE10LR1/2ED	10	G 1/2 A	13.0	27	315	315		315	315
GE12LR1/4ED	12	G 1/4 A	12.0	19	315	315		315	315
GE12LRED	12	G 3/8 A	12.5	22	315	315		315	315
GE12LR1/2ED	12	G 1/2 A	13.0	27	315	315		315	315
GE15LR3/8ED	15	G 3/8 A	13.5	24	315	315		315	315
GE15LRED	15	G 1/2 A	14.0	27	315	315		315	315
GE18LRED	18	G 1/2 A	14.5	27	315	315		315	315
GE18LR3/4ED	18	G 3/4 A	14.5	32	315	315		315	315
GE22LRED	22	G 3/4 A	16.5	32	160	160		160	160
GE28LRED	28	G 1 A	17.5	41	160	160		160	160
GE35LRED	35	G 1 1/4 A	17.5	50	160	160		160	160
GE42LRED	42	G 1 1/2 A	19.0	55	160	160		160	160
GE06SRED	6	G 1/4 A	13.0	19	630	630		630	630
GE08SRED	8	G 1/4 A	15.0	19	630	630		630	630
GE08SR3/8ED	8	G 3/8 A	15.5	22	630	630		630	630
GE10SR1/4ED	10	G 1/4 A	14.5	19	630	630		630	630
GE10SRED	10	G 3/8 A	15.0	22	630	630		630	630
GE10SR1/2ED	10	G 1/2 A	17.5	27	630	630		630	630
GE12SR1/4ED	12	G 1/4 A	16.5	22	630	630		630	630
GE12SRED	12	G 3/8 A	17.0	22	630	630		630	630
GE12SR1/2ED	12	G 1/2 A	17.5	27	630	630		630	630
GE14SRED	14	G 1/2 A	19.0	27	630	630		630	630
GE16SR3/8ED	16	G 3/8 A	18.0	27	400	400		400	400
GE16SRED	16	G 1/2 A	18.5	27	400	400		400	400
GE16SR3/4ED	16	G 3/4 A	20.5	32	400	400		400	400
GE20SRED	20	G 3/4 A	20.5	32	400	400		400	400
GE25SR1/2ED	25	G 1/2 A	23.0	41	400	400		400	400
GE25SRED	25	G 1 A	23.0	41	400	400		400	400
GE30SRED	30	G 1 1/4 A	23.5	50	400	400		400	400
GE38SRED	38	G 1 1/2 A	26.0	55	315	315		315	315

For EO-2 part number, insert "Z" between size and pressure series.
Example: GE06ZLREDA3C