



Search within category GO

PSM7004BU-KEM



Shielded marine copper cable, category 7 S/FTP, low smoke zero halogen (LSZH), 4-pair, conductors are 4 x 2/0.27mm2, twisted in pairs, each individual twisted pair is surrounded by a foil, covered with an overall braided shield and is protected by an oil- and fuel-resistant, low smoke zero halogen (LSZH) (IEC 60332-3c) jacket, blue.
 Available in all regions

BUY NOW

DESIGN / INSTALL

Specs	Packaging Details	Documents
Color	Blue	
AWG Size	23	
Length (ft.)	3280	
Length (m)	1000	
Nominal Diameter (In.)	0.314	
Nominal Diameter (mm)	7.9	
Jacket Material	High Density Polyethylene	
No. of Pairs	4	
Installation Temperature	-15°C to 50°C (5°F to 122°F)	
Operating Temperature	-40°C to 85°C (-40°F to 185°F)	
Packaging Type	Reel	
Application	Harsh Environment; Indoor; Marine; Oil/Gas	
Cable Type	S/FTP	
Flammability Rating	LSZH-3 (60332-3)	
Installation Tension	100N (22 lbf)	
Insulation Diameter (In.)	0.060-0.063	
Insulation Diameter (mm)	1.52-1.60	
Note	Available in all regions	
Part Features	23 AWG stranded conductor wire, individually foiled pairs with overall braided shield, robust jacketing and tested beyond the strands	
Performance Level	Category 7	
Sub Brand	PanNet	
RoHS Compliancy Status	Compliant	
Min. Order Qty.	4	

★ Add to Favorites Add to BOM