



<b>EAN:</b>	4013288099532	<b>Size:</b>	50x7x7 mm
<b>Part number:</b>	05066688001	<b>Weight:</b>	12 g
<b>Article number:</b>	871/4 DC TORQ-SET® Mplus	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82079030

- For TORQ-SET® screws
- Mplus for more breaking torque and longer service life
- Diamond coating for a secure fit in the screw, literally bites into the screwhead to prevent cam-out
- 1/4" hexagon drive (Wera connecting series 4)
- Suitable for AEG, ARO, Atlas-Copco, Biax, Black & Decker, Bosch, Buckeye Tools etc.

High quality bits for TORQ-SET® screws. The stronger flanks – when compared with the conventional TORQ-SET profile – result in 70% more breaking torque and thereby enhanced durability whilst at the same time providing a perfect fit in the screw head. The diamond coating of the bit ensures a secure fit in the screw, reduces the contact pressure required and lowers the risk of slipping. 1/4" hexagon, suitable for holders as per DIN ISO 1173-F 6.3.


### Web link

[http://products.wera.de/en/tools\\_for\\_the\\_aerospace\\_segment\\_the\\_range\\_of\\_bits\\_bits\\_for\\_torq-set\\_screws\\_871\\_4\\_dc\\_torq-set\\_mplus.html](http://products.wera.de/en/tools_for_the_aerospace_segment_the_range_of_bits_bits_for_torq-set_screws_871_4_dc_torq-set_mplus.html)

Wera - 871/4 DC TORQ-SET® Mplus  
05066688001 - 4013288099532

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

## TORQ-SET® Mplus



Wera developed the Mplus profile with stronger flanks compared with tools with a conventional TORQ-SET® profile. This results in approximately 70 % extra torsional strength and greatly extends the service life of Wera Mplus tools.

## Bits with diamond coating




The diamond coating of the DC bits lowers the danger of slipping as the minute diamond particles literally "bite" themselves into the screw head.

## Secure fit in the screw head




Today, the Wera diamond bit – manufactured with the technology specifically developed by Wera for this application – still sets the standard in terms of resilience and functionality. Wera bits with a diamond coating ensure a secure fit of the bit in the screw head.

## Reduced cam-out forces







The minute diamond particles applied to the tip of the tool literally "bite" into the screw and ensure an exact, anti-slip fit in the head of the screw. This secure fit protects the screw. The cam-out forces which compel the user to apply greater pressure to the screw are considerably reduced.

## Perfect fit



Ideal for sensitive materials

## Further versions in this product family:

				
		inch	mm	inch
05324901001	2		50	2
<b>05066688001</b>	<b>4</b>		<b>50</b>	<b>2</b>
05066690001	6		50	2
05066692001	8		50	2
05066694001	10		50	2
05066696001	--	1/4	50	2
05344515001	--	5/16"	50	2

## Web link

[http://products.wera.de/en/tools\\_for\\_the\\_aerospace\\_segment\\_the\\_range\\_of\\_bits\\_bits\\_for\\_torque\\_set\\_screws\\_871\\_4\\_dc\\_torque-set\\_mplus.html](http://products.wera.de/en/tools_for_the_aerospace_segment_the_range_of_bits_bits_for_torque_set_screws_871_4_dc_torque-set_mplus.html)

Wera - 871/4 DC TORQ-SET® Mplus  
 05066688001 - 4013288099532

Wera Werkzeuge GmbH  
 Korzter Straße 21-25  
 D-42349 Wuppertal  
 Tel: +49 (0)2 02 / 40 45-0  
 E-Mail: [info@wera.de](mailto:info@wera.de)

871/4 DC TORQ-SET® Mplus bits, 4 x 50 mm

Bits for TORQ-SET® Screws



**Web link**

[http://products.wera.de/en/tools\\_for\\_the\\_aerospace\\_segment\\_the\\_range\\_of\\_bits\\_bits\\_for\\_torq-set\\_screws\\_871\\_4\\_dc\\_torq-set\\_mplus.html](http://products.wera.de/en/tools_for_the_aerospace_segment_the_range_of_bits_bits_for_torq-set_screws_871_4_dc_torq-set_mplus.html)

Wera - 871/4 DC TORQ-SET® Mplus  
05066688001 - 4013288099532

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)