



**Part Number :** [1719832342](#)

**Product Description :** Nano-Pitch I/O Connector, Vertical, Through Hole, with Cap, 42 Circuits, Shell Leg Length 3.00mm, Natural

**Series Number :** 171983

**Status :** Active

**Product Category :** High-Speed I/O Connectors



---

## Documents & Resources

### Drawings

[Drawing 1719832342\\_sd.pdf](#)

[Packaging Design Drawing PK-171982-9000-001.pdf](#)

[Packaging Design Drawing PK-173307-0001-001.pdf](#)

### 3D Models and Design Files

[3D Model 1719832342\\_stp.zip](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Active
Category	High-Speed I/O Connectors
Series	171983
Description	Nano-Pitch I/O Connector, Vertical, Through Hole, with Cap, 42 Circuits, Shell Leg Length 3.00mm, Natural
Application	Wire-to-Board
Component Type	Receptacle
Product Family	Nano-Pitch I/O Interconnect System
Product Name	Nano-Pitch I/O
Type	Internal
UPC	191128136464

### Agency

UL	E29179
----	--------

### Electrical

Current - Maximum per Contact	0.5A
Data Rate	16.0 Gbps
Grounding to Panel	None
Shielded	No
Voltage - Maximum	30V AC (RMS)/DC

### Physical

Circuits (Loaded)	42
Circuits (maximum)	42
Color - Resin	Natural
Durability (mating cycles max)	250
Gender	Receptacle

Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	0.750/g
Number of Rows	2
Orientation	Vertical
Packaging Type	Embossed Tape on Reel
Panel Mount	No
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.57mm
Pitch - Mating Interface	0.50mm
Pitch - Termination Interface	0.50mm
Plating min - Mating	0.762μm
Plating min - Termination	2.540μm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Ports	1
Temperature Range - Operating	-40° to +80°C
Termination Interface Style	Through Hole