



Part Number : [1731120208](#)

Product Description : FCT Machined Contact, Male, Crimp, 1.30µm Gold Plating, 28-26 AWG, 500 Pieces

Series Number : 173112

Status : Active

Product Category : D-Sub Contacts

Engineering Number : FK20P26-13V-5783



---

## Documents & Resources

### Drawings

[1731120208\\_sd.pdf](#)

### Specifications

[1731120004-PK-000.pdf](#)

[2195600650-000.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Active
Category	D-Sub Contacts
Series	173112
Description	FCT Machined Contact, Male, Crimp, 1.30µm Gold Plating, 28-26 AWG, 500 Pieces
Contact Type	Machined Crimp
Magnetic	Yes
Product Name	FCT Products
Type	Standard Density
UPC	889056489638

### Electrical

Current - Maximum per Contact	7.5A
-------------------------------	------

### Physical

Durability (mating cycles max)	500
Gender	Male
Material - Contact	Brass
Material - Plating Mating	Gold over Nickel
Material - Plating Termination	Gold over Nickel
Net Weight	1.000/g
Orientation	Straight
Packaging Type	Bag
Plating min - Mating	1.300µm
Plating min - Termination	1.300µm
Temperature Range - Operating	-55° to +130°C

Termination Style	Crimp
Wire Size (AWG)	26, 28

---

### Use with Part(s)

Description	Part Number
Use With	FCT Standard-Density Connectors

---

### Application Tooling

#### Global

Description	Part Number
FCT Hand Crimp Tool, Mini Frame, 8-Step Adjust	<u>1731121730</u>
FCT Locator for Size 20 Contacts, Plug and Socket	<u>1731121733</u>
FCT Installation and Removal Tool for D-Subs	<u>1731121744</u>

---