


SIGN	DATE	DESCRIPTION	APPROVER
△	02/07'06	Part No. changed	Tony
△	2010.03.23	Add the 2p mark	Jacke
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

Material

- Item a Clamp: Steel zinc plated.
- Item b Terminal screw: Steel Zinc plating "--" slot type
- Item c Female contact: PhBz Tin plated
- Item d Terminal (Up body): Thermoplastic (UL94V-0)
- Item e Terminal (Down body): Thermoplastic (UL94V-0)
- Item f Clampage: Steel Zinc plated

Electrical cULus/TUV

- Voltage rating: 300VAC/300VAC
- Current rating: 20A/20A
- Wire range: 0.34-2.5mm²
- Solid wire(AWG): 12-22
- Stranded wire(AWG): 12-22
- Torque: 3.5Lb-In / 0.4Nm
- Screw: M2.5
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV/2.5KV
- Operating temperature: -40°C to +115°C
- Safety approval: 


VM xx 7 5 x 0 xxxx G





POLES	Color	G: Pb<40000ppm
02 pole		
24 pole		
	0 Black (RAL9005)	0000: Standard (Steel screw plating Cr ^{III})
	2 Red (RAL3001/D)	000A: "ANYTEK" Mark
	3 Orange(RAL2011/P)	Any special item by customer request.
	4 Yellow(RAL1018/A)	please contact sales department.
	5 Green(RAL6018/T)	
	6 Blue (RAL5015/A)	
	8 Grey(RAL7035/D)	

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	VM 5.0mm W/O Flange Series						
PART NO.	VMxx75x0xxxxG			DWG NO.	8VM0001		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance		
		Jacke 2010.03.23	Tony 2006.02.07		UNIT: mm	X.	±0.50
					SCALE: NONE	X.X	±0.30
						X.XX	±0.10
						X°	±1°
				SHEET: 01/01	REV.: E		



POLE		2	3	4	5	6	7	8	9	10	11	12
A		10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00
B		5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00
Tol.		±0.20					±0.25					
POLE	13	14	15	16	17	18	19	20	21	22	23	24
A	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.00	110.00	115.00	120.00
B	60.00	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.00	110.00	115.00
Tol.		±0.30					±0.40					

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

<u>VM0275500000G</u>	<u>VM0375500000G</u>	<u>VM0475500000G</u>	<u>VM0575500000G</u>	<u>VM0675500000G</u>	<u>VM0775500000G</u>
<u>VM0875500000G</u>	<u>VM0975500000G</u>	<u>VM1075500000G</u>	<u>VM1175500000G</u>	<u>VM1275500000G</u>	<u>VM1375500000G</u>
<u>VM1475500000G</u>	<u>VM1575500000G</u>	<u>VM1675500000G</u>	<u>VM1775500000G</u>	<u>VM1875500000G</u>	<u>VM1975500000G</u>
<u>VM2075500000G</u>	<u>VM2175500000G</u>	<u>VM2275500000G</u>	<u>VM2375500000G</u>	<u>VM2475500000G</u>	<u>VM0375800000G</u>
<u>VM0275000000G</u>	<u>VM0475800000G</u>	<u>VM0675000000G</u>	<u>VM0275800000G</u>	<u>VM0575000000G</u>	<u>VM0575800000G</u>
<u>VM0875000000G</u>	<u>VM1275000000G</u>	<u>VM2275800000G</u>	<u>VM2075800000G</u>	<u>VM2175800000G</u>	<u>VM2475800000G</u>
<u>VM1975800000G</u>	<u>VM0375000000G</u>	<u>VM0475000000G</u>	<u>VM1375800000G</u>	<u>VM2375800000G</u>	<u>VM2175000000G</u>
<u>VM2275000000G</u>	<u>VM2475000000G</u>	<u>VM1775800000G</u>	<u>VM1675800000G</u>	<u>VM1675000000G</u>	<u>VM1375000000G</u>
<u>VM1875000000G</u>	<u>VM1975000000G</u>	<u>VM2075000000G</u>	<u>VM2375000000G</u>	<u>VM0975800000G</u>	<u>VM1075800000G</u>
<u>VM1475000000G</u>	<u>VM1575000000G</u>	<u>VM1275800000G</u>	<u>VM1075000000G</u>	<u>VM1575800000G</u>	<u>VM0975000000G</u>
<u>VM1175000000G</u>	<u>VM0775800000G</u>	<u>VM1775000000G</u>	<u>VM0675800000G</u>	<u>VM0775000000G</u>	<u>VM0875800000G</u>
<u>VM1175800000G</u>	<u>VM1475800000G</u>	<u>VM1875800000G</u>			