

Designed to IEC standard for world-wide applications
 UL, CSA, and CE
 International conduit sizes
 Direct PLC interface compatible (two circuit)
 Modular construction reduces maintenance parts costs
 Designed for ease of installation
 Variety of basic switch versions
 Wide choice of actuators

Machine tools: metal fabrication equipment, presses, transfer lines and special machinery
 Material handling equipment: conveyors, elevators, cranes, and hoists
 Packaging machinery and process equipment
 Textile machinery
 Construction machinery and equipment, vehicles and lift trucks

Use (*) to expand

Specific

Description

The GLS series limit switches are specifically designed for world-wide applications and are supported by Honeywell global resources for sale and after sale service.

Supporting Documentation

 [Installation Instructions](#)

 [Instructions for reading bar charts](#)

 [Engineering Drawing](#)

Product Specifications	
Availability	Global
Operating Force (O.F.)	0,330 N m [2.90 in lb]
Pretravel (P.T.)	26°
Overtravel (O.T.)	59°
Differential Travel (D.T.)	12°
Product Type	EN50041/47 Global Limit Switch
Actuator	Side Rotary
Lever Style	-- No Lever --
Circuitry	1NC 1NO SPDT Snap Action
Ampere Rating	10 A (Thermal)
Supply Voltage	600 Vac and 250 Vdc max.
Housing Material	Zinc Die-Cast
Termination Type	20 mm
Housing Type	EN 50041
Series Name	GLS DIN
Shock	50 g per IEC 68-2-27c (w/o Actuator)
Vibration	10 g per IEC 68-2-6 (w/o Actuator)
Sealing	NEMA 1, 4, 12, 13 IP67
Approvals	UL, CSA, CE
CSA File #	LR94369-3
UL File #	E37138 & E157416
Mechanical Life	15 million
Operating Temperature Range	-25 °C to 85 °C [-13 °F to 185 °F]
Agency Approvals and Standards	IEC 947-5-1, EN60947-5-1, UL508
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Industrial
Operating Position (O.P.)	26°