


Product description	<b>Snap-In Female angled connector, Contacts: 3, unshielded, PUR, black, 3 x 0.14 mm<sup>2</sup></b>
Area	<b>series 718</b>
Part no.	<b>79 3414 15 03</b>


### Illustration



### Scale drawing



### Contact arrangement (Plug-in side)



## Technical data

### General features

Part no.	<b>79 3414 15 03</b>
Connector design	Female angled connector
Type standard	DIN EN 61076-2-104
Version	Connector socket angled
Connector locking system	snap-in
Weight (g)	67.50
Customs tariff number	85444290
Country of Origin	DE

### Electrical parameters

Rated voltage	50 V (AC) / 60 V (DC)
EMC compliance	unshielded

### Material

Housing material	PUR
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	f4fd05d7-6fde-4822-b511-80374756cddb

### Classifications

eCl@ss 11.1	27-06-03-11
ETIM 9.0	EC002638

### Declarations of conformity

Low Voltage Directive	2014/35/EU (EN 60204-1:2018;EN 60529:1991)
-----------------------	--

# Product data sheet

## Automation technology - Sensors and actuators



Product description	<b>Snap-In Female angled connector, Contacts: 3, unshielded, PUR, black, 3 x 0.14 mm<sup>2</sup></b>
Area	<b>series 718</b>
Part no.	<b>79 3414 15 03</b>

RoHS Directive 2011/65/EU (EN 50581:2012)

### Cable data - Structure of the cable

Cable diameter	5.0 mm
Cross section	3 x 0.14 mm <sup>2</sup>
Sheath material	PUR
Single-lead insulation	PVC
Single-lead structure	7 x 0.25 mm
Cable color	black

### Cable data - Electrical properties

Conductor resistance	148 Ω/Km (20°C)
----------------------	-----------------

### Cable data - Mechanical properties

Travel distance, horizontal	2 m/s <sup>2</sup> -> 3 m
-----------------------------	---------------------------

### Cable data - Thermal properties

Temperature range cable in move from/to	-5 °C / 70 °C
Temperature range cable fixed from/to	-25 °C / 70 °C

### Cable data - Other features

Halogen free	no
--------------	----

Product description	<b>Snap-In Female angled connector, Contacts: 3, unshielded, PUR, black, 3 x 0.14 mm<sup>2</sup></b>
Area	<b>series 718</b>
Part no.	<b>79 3414 15 03</b>

## Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

The plug connector is not suitable for mains voltages. Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 40 cNm).