

GA aluminum screw cover junction box



GA accessories Page 35 System accessories Page 531

Material:
– Enclosure: Cast aluminum
– Cover: Cast aluminum,
all-round foamed-in PU seal


Surface finish:
Textured paint

Color:
RAL 7001

Protection rating:
NEMA 4/4X (IP 66 to EN 60
529/09.2000)

Configuration:
– Enclosure with cover
– Cover screws, captive
– Screws for attaching support
rails
– Screw for connection of the
PE conductor

Detailed drawings:
Available at www.rittal-corp.com



Depth: 1.2 - 3.2" (30 - 80 mm), Height: 1.8 - 4.7" (45 - 120 mm)

Height (H1) inches (mm)	1.8 (45)	2.5 (64)	2.5 (64)	2.5 (64)	3.2 (80)	3.2 (80)	3.2 (80)	3.2 (80)	4.7 (120)
Width (B1) inches (mm)	2.0 (50)	2.3 (58)	3.9 (98)	5.9 (150)	3.0 (75)	4.9 (125)	6.9 (175)	9.8 (250)	4.8 (122)
Depth (T1) inches (mm)	1.2 (30)	1.4 (36)	1.4 (36)	1.4 (36)	2.3 (57)	2.3 (57)	2.3 (57)	2.3 (57)	3.2 (80)
Part No.	9100.210	9101.210	9102.210	9103.210	9104.210	9105.210	9106.210	9107.210	9108.210
PU	6	5	3	2	1	1	1	1	1

Accessories

Mounting panel	–	9105.700	–	9108.700
PU	–	10	–	2
Support rail ¹⁾ TS 15/5.5 (PU 10)	–	9105.150	–	
TS 35/7.5 (PU 5)	–			9108.350
Wall mounting brackets (PU 2)	–			9121.122
Exterior hinge (PU 2)	–			9123.000

¹⁾ Installation in the width

Depth: 3.5 - 7.1" (90 - 180 mm), Height: 4.7 - 9.1" (120 - 230 mm)

Height (H1) inches (mm)	4.7 (120)	4.8 (122)	6.3 (160)	6.3 (160)	6.3 (160)	9.1 (230)	9.1 (230)	9.1 (230)	9.1 (230)
Width (B1) inches (mm)	8.7 (220)	14.2 (360)	6.3 (160)	10.2 (260)	14.2 (360)	7.9 (200)	11.0 (280)	13.0 (330)	13.0 (330)
Depth (T1) inches (mm)	3.5 (90)	3.2 (80)	3.5 (90)	3.5 (90)	3.5 (90)	4.3 (110)	4.3 (110)	4.3 (110)	7.1 (180)
Part No.	9110.210	9111.210	9112.210	9113.210	9114.210	9116.210	9117.210	9118.210	9119.210
PU	1	1	1	1	1	1	1	1	1

Accessories

Mounting panel	9110.700	–	9112.700	9113.700	9114.700	9116.700	9117.700	9118.700	9118.700
PU	2	–	2	2	1	1	1	1	1
Support rail ¹⁾ TS 35/7.5 (PU 5)	9110.350	–	9112.350						
Wall mounting brackets (PU 2)	9121.122		9121.160				9121.230		
Exterior hinge (PU 2)							9123.000		

¹⁾ Installation in the width