

# 1880 MHz SMD SAW Filter

**ABSNS6A7-368M02CM**

Request Samples



Check Inventory



**3.0 x 3.0 x 1.3 mm**  
**RoHS Compliant**


## Features

- Bandpass SAW Filter with 60 MHz bandwidth
- Surface Mount 3.0 x 3.0 x 1.3 mm package
- Single-Ended Input and Output
- Excellent selectivity with high out-of-band rejection

## Applications

- Base Station Applications
- Wireless infrastructure
- Distributed Antenna Systems (DAS)
- Wireless Repeaters

## Product Image



# 1880 MHz SMD SAW Filter

ABSNS6A7-368M02CM

Request Samples



Check Inventory



3.0 x 3.0 x 1.3 mm  
RoHS Compliant

## Electrical Specification

Parameters	Minimum	Typical	Maximum	Units	Notes
Center Frequency (fc)	-	1880	-	MHz	
Insertion Loss	-	3.0	4.0	dB	1850 – 1910 MHz
Amplitude Ripple	-	1.7	2.5	dB <sub>p-p</sub>	1850 – 1910 MHz
Attenuation	20	32	-	dB	D.C.~1660 MHz
	25	32	-		1660~1721 MHz
	20	37	-		1721~1800 MHz
	7	19	-		1930~1990 MHz
	25	37	-		2000~2040 MHz
	31	38	-		2040~2480 MHz
	25	28	-		3700~3820 MHz
VSWR	-	1.8	2.0	-	1850 – 1910 MHz
DC Voltage	-	-	5	V	
Input Power	-	-	10	dBm	
Source Impedance (single ended)1	-	50	-	Ω	
Load Impedance (single ended)1	-	50	-	Ω	

Notes: (1) No Matching Network (Ref. Testing Environment Circuit as shown below)

## Mechanical Specification

Parameters	Specifications
Dimension	3.0 x 3.0 x 1.3 mm
Mounting Type	SMD Mount

## Environmental Specification

Parameters	Specifications
Operating Temperature Range	-30°C ~ +85°C
Storage Temperature Range	-40°C ~ +85°C
MSL level	N/A
ESD	N/A



5101 Hidden Creek Ln Spicewood TX 78669  
Phone: 512-371-6159 | Fax: 512-351-8858  
For terms and conditions of sales, please visit:  
www.abracon.com

REVISED: 06-15-23

ABRACON IS  
ISO9001-2015  
CERTIFIED

# 1880 MHz SMD SAW Filter

ABSNS6A7-368M02CM

Request Samples




Check Inventory



3.0 x 3.0 x 1.3 mm  
RoHS Compliant

## Product Dimensions



Unit : mm

Pin No.	Description
A,C,D,F	Ground
E	Input
B	Output

# 1880 MHz SMD SAW Filter

ABSNS6A7-368M02CM

Request Samples




Check Inventory



3.0 x 3.0 x 1.3 mm  
RoHS Compliant

## Measurement Circuit



Source & Load Impedance: 50  $\Omega$

# 1880 MHz SMD SAW Filter

ABSNS6A7-368M02CM

Request Samples




Check Inventory




3.0 x 3.0 x 1.3 mm  
RoHS Compliant

## Frequency Characteristics

S21 narrow band



S21 wide band



# 1880 MHz SMD SAW Filter

**ABSNS6A7-368M02CM**

Request Samples




Check Inventory



**3.0 x 3.0 x 1.3 mm**  
**RoHS Compliant**

## Group Delay Ripple



# 1880 MHz SMD SAW Filter

ABSNS6A7-368M02CM

Request Samples





Check Inventory



3.0 x 3.0 x 1.3 mm  
RoHS Compliant

## VSWR (S11 & S22)



# 1880 MHz SMD SAW Filter

ABSNS6A7-368M02CM

Request Samples




Check Inventory




3.0 x 3.0 x 1.3 mm  
RoHS Compliant

Smith Chart (S11 & S22)

Smith chart S11 (1840~1912MHz)



Smith chart S22 (1840~1912MHz)





# 1880 MHz SMD SAW Filter

ABSNS6A7-368M02CM

Request Samples



Check Inventory



3.0 x 3.0 x 1.3 mm  
RoHS Compliant

## Reflow Profile [JEDEC J-STD-020]




Table 1

### SnPb Eutectic Process Classification Temperatures ( $T_c$ )

Package Thickness	Volume mm <sup>3</sup> <350	Volume mm <sup>3</sup> ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2

### Pb-Free Process Classification Temperatures ( $T_c$ )

Package Thickness	Volume mm <sup>3</sup> <350	Volume mm <sup>3</sup> 350-2000	Volume mm <sup>3</sup> >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 mm - 2.5 mm	260 °C	250 °C	245 °C
>2.5 mm	250 °C	245 °C	245 °C

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat / soak		
Temperature minimum ( $T_{smin}$ )	100°C	150°C
Temperature maximum ( $T_{smax}$ )	150°C	200°C
Time ( $T_{smin}$ to $T_{smax}$ ) ( $t_s$ )	60 - 120 sec.	60 - 120 sec.
Average ramp-up rate ( $T_{smax}$ to $T_p$ )	3°C/sec. max	3°C/sec. max
Liquidous temperature ( $T_L$ )	183°C	217°C
Time at liquidous ( $t_L$ )	60 - 150 sec.	60 - 150 sec.
Peak package body temperature ( $T_p$ )*	see Table 1	see Table 2
Time ( $t_p$ )** within 5°C of the specified classification temperature ( $T_c$ )	20 sec.	30 sec.
Ramp-down rate ( $T_p$ to $T_{smax}$ )	6°C/sec. max	6°C/sec. max
Time 25°C to peak temperature	6 min. max	8 min. max
Reflow cycles	2 max	2 max

\*Tolerance for peak profile temperature ( $T_p$ ) is defined as a supplier minimum and a user maximum.

\*\*Tolerance for time at peak profile temperature ( $t_p$ ) is defined as supplier minimum and a user maximum.

# 1880 MHz SMD SAW Filter

**ABSNS6A7-368M02CM**

Request Samples




Check Inventory



**3.0 x 3.0 x 1.3 mm**  
RoHS Compliant

## Packaging

### Tape & Reel Dimension



### Carrier Tape Specifications (mm)

E1	P0	F	P1	W	A0	B0	K0	Reel Qty
1.75 ± 0.1	4.0 ± 0.1	5.5 ± 0.10	8.0 ± 0.1	12.0 ± 0.3	3.4 ± 0.1	3.4 ± 0.1	1.4 ± 0.1	2,500

### Reel Specifications (mm)

A	W <sub>1</sub>	N	C
330 ± 1.0	12.0 ± 1.0	62 ± 1.0	13 ± 0.5

**ATTENTION:** Abracon LLC's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon LLC is required. Please contact Abracon LLC for more information.



5101 Hidden Creek Ln Spicewood TX 78669  
Phone: 512-371-6159 | Fax: 512-351-8858  
For terms and conditions of sales, please visit:  
[www.abracon.com](http://www.abracon.com)

**REVISED: 06-15-23**

ABRACON IS  
ISO9001-2015  
CERTIFIED