



- NOTES:
- HUOSING:LCP HIGH-TEMP THERMOPLASTIC UL94V-0 COLOR:BLACK
 - TERMINAL/GROUND PLANE:PHOSPHOR BRONZE
PLATING:10 μ GOLD IN CONTACT AREA, MATTE TIN ON TALL.
 - Operating Temp Range: -55 to +125
 - Current Rating:
Contact :2A per pin
Ground Plane :25A per ground plane
 - Voltage Rating :175 VAC
 - Max Cycles :175 VAC

NO. of contacts	Dimensions		
	A.	B.	C.
40	20.00	18.48	0.10
80	40.00	38.48	0.10
120	60.00	58.48	0.15

PART NO:
PART NO: BHTH 05 - XXX V01 G10 DP T

220: 40PIN
240: 80PIN
260: 120PIN

G10: Au 10 μ /Tin

OPERATION										MODIFICATION DESCRIPTION	
DIM	TOL			SCALE	FIT						
X.X	± 0.30	DRAW	LIUSHENGYU								
X.XX	± 0.13	DESIGN	LIUSHENGYU	UNIT	mm	PART NO.	BHTH05- XXXV01G10DPT				
X.XXX	± 0.05	CHECK	LVHAIXIN	SIZE	A4	TITLE:	0.50mm DOUBLE ROW BTB SOCKET H3.25				
Angle	$\pm 3^\circ$	APPROVE	LVHAIXIN	SHEET	1/2						
		REV	A0	PROJ.							