



Electronics module for IO-Link, black, 8 inputs/outputs, 6 DI/2 DQ, Push-in, for floor mounting

product brand name	SIRIUS ACT
product designation	Electronic module for IO-Link
product type designation	3SU1
General technical data	
insulation voltage rated value	30 V
degree of pollution	3
type of voltage	
• of the operating voltage	DC
• of the input voltage	DC
surge voltage resistance rated value	0.8 kV
consumed current maximum	41 mA
protection class IP	IP20
shock resistance for railway applications acc. to DIN EN 61373	Category 1, Class B
vibration resistance for railway applications acc. to DIN EN 61373	Category 1, Class B
reference code acc. to IEC 81346-2	P
• operating voltage rated value	18 ... 30 V
operating voltage 1 at DC rated value	24 V
Communication/ Protocol	
protocol is supported	
• AS-Interface protocol	No
• IO-Link protocol	Yes
IO-Link transfer rate	COM2 (38,4 kBaud)
point-to-point cycle time between master and IO-Link device minimum	10 ms
type of voltage supply via input/output link master	Yes
data volume	
• of the address range of the inputs with cyclical transfer total	3 byte
• of the address range of the outputs with cyclical transfer total	1 byte
Inputs/ Outputs	
number of digital inputs	6
number of digital outputs	2
Connections/ Terminals	
type of electrical connection	Push-in terminal
type of connectable conductor cross-sections	

- solid with core end processing
- solid without core end processing
- finely stranded without core end processing
- at AWG cables

1x (0.14 ... 0.5 mm²)
 1x (0.14 ... 0.5 mm²)
 1x (0.2 ... 0.5 mm²)
 1x (26 ... 20)

Product Function

suitability for use safety-related circuits No

Ambient conditions

- ambient temperature during operation -25 ... +70 °C
- ambient temperature during storage -40 ... +80 °C

environmental category during operation acc. to IEC 60721 3M6, 3S2, 3B2, 3C3 (without salt spray), 3K6 (with relative humidity of 10 ... 95%, no condensation in operation permitted)

Installation/ mounting/ dimensions

fastening method of modules and accessories Floor mounting

height 57.5 mm

width 23.8 mm

depth 53.5 mm

Measuring circuit

product function 6DI / 2DO

Certificates/ approvals

General Product Approval

Declaration of Conformity

Test Certificates

other



[Miscellaneous](#)



EG-Konf.

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1400-2HK10-6AA0>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1400-2HK10-6AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1400-2HK10-6AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1400-2HK10-6AA0&lang=en



last modified:

12/23/2020 [🔗](#)