



FEATURES

- For surface mounted applications
- Fast reverse recovery time
- Ideal for automated placement

MECHANICAL DATA

- Case: SOD-323W
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 5.48mg / 0.00019oz

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Top View

Simplified outline SOD-323W and symbol

Absolute Maximum Ratings at 25 °C

Parameter	Symbols	1N4448WS	Units
Non-Repetitive Peak Reverse Voltage	V_{RM}	100	V
Peak Repetitive Reverse Voltage	V_{RRM}		
Working Peak Reverse Voltage	V_{RWM}	75	V
DC Reverse Voltage	V_R		
RMS Reverse Voltage	$V_{R(RMS)}$	53	V
Forward Continuous Current	I_{FM}	500	mA
Average Rectified Output Current	I_o	250	mA
Non-Repetitive Peak Forward Surge Current @t=1.0 μs @t=1.0 s	I_{FSM}	4.0 2.0	A
Power Dissipation	P_d	200	mW
Thermal Resistance Junction to Ambient Air	R_{thJA}	625	°C/W
Operating and Storage Temperature Range	T_j, T_{stg}	-65 ~ +150	°C

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbols	1N4448WS	Units
Reverse Breakdown Voltage at $I_R=1.0\mu\text{A}$	$V_{(BR)R}$	75(min)	V
Forward Voltage at 5 mA at 10 mA at 100 mA at 150 mA	V_F	0.62(min) 0.72(max) 0.855(max) 1.00(max) 1.25(max)	V
Peak Reverse Current at $V_R=75\text{V}$ at $V_R=20\text{V}$	I_R	2.5(max) 25(max)	μA nA
Typical Junction Capacitance f=1MHz, $V_R=0\text{V}$	C_j	4(max)	pF
Maximum Reverse Recovery Time ⁽¹⁾	t_{rr}	4	ns

(1) Measured with $I_F=I_R=10\text{mA}$, $I_{rr}=0.1 \times I_R$, $R_L=100\Omega$



Fig.1 Power Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Instaneous Forward Characteristics





Fig.4 Typical Junction Capacitance







PACKAGE OUTLINE

Plastic surface mounted package; 2 leads

SOD-323W



The recommended mounting pad size



Marking

Type number	Marking code
1N4448WS	T5