

Part Number: 314022110 Product Description: 2.54mm MX64 Sealed

Single Row Crimp Housing, GET Terminal, Black, 2 Circuits, Key A, with CPA Lock

Series Number: 31402 Status: Active

Product Category: Connector Housings Engineering Number: CVP-314022110

Documents & Resources

Drawings

Drawing 314022110_sd.pdf

Packaging Design Drawing PK-31300-256-001.pdf

3D Models and Design Files

3D Model 314022110_stp.zip

Specifications

Application Specification 314020000-000.pdf
Application Specification AS-31402-000-001.pdf
Product Specification PS-31402-000-001.pdf
Test Summary TS-31402-001-1X2-001.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant
China RoHS	©
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Dodecamethylcyclohexasiloxane; Decamethylcyclopentasiloxane; Octamethylcyclotetrasiloxane per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Connector Housings
Series	31402
Description	2.54mm MX64 Sealed Single Row Crimp Housing, GET Terminal, Black, 2 Circuits, Key A, with CPA Lock
Application	Power, Wire-to-Board
Product Family	MX64 Sealed Connectors
Product Name	MX64
UPC	822348656622

Physical

Circuits (maximum)	2
Color - Resin	Black
Gender	Receptacle
Glow-Wire Capable	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	PBT
Net Weight	4.710/g
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	2.54mm
Polarization	А
Polarized to Mating Part	Yes

Temperature Range - Operating	-40° to +125°C

Solder Process Data

Lead-Free Process Capability	N/A
=======================================	

Mates With / Use With

Mates with Part(s)

Description	Part Number
Mates With	Sensors, Other USCAR Interfaces

This document was generated on Sep 15, 2024