

M12 Connector

TE Internal #: 6-2271116-2

Cable-to-Cable, 12 Position, Sealable, Wire & Cable, Signal, Cable Mount (Free-Hanging), Reverse Gender, M12 Connector, Standard

Circular Connectors

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Cable-to-Cable

Connector Mounting Type: Cable Mount (Free-Hanging)

Number of Positions: 12

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Features

Product Type Features

Product Type Features	
Product Type	Connector Assembly
Accessory Color	Black
Assembly Requirement	Factory Assembled
Assembly Type	Electrical Connector
Circular Connector Shell Type	All Plastic
Connector Product Type	Connector Assembly
Connector System	Cable-to-Cable
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Circular Connector Type	Receptacle
Shell Type	Plastic
Configuration Features	
Number of Positions	12
Number of Power Positions	0



Number of Signal Positions	12
Contacts Preloaded	Yes
Electrical Characteristics	
EMI & RFI Protection & Suppression Type	Shielding
Body Features	
Shell Plating Material	Unplated
Shell Base Material	Plastic
Circular Connector Insulation Material Type	PA
Hermetically Sealed	Yes
Contact Features	
Contact Current Rating (Max)	2 A
Reverse Gender	Yes
Circular Connector Contact Type	Socket
Mechanical Attachment	
Connector Mounting Type	Cable Mount (Free-Hanging)
Polarization Code	A
Mating Alignment Type	Keyed
Mating Alignment Type Housing Features	Keyed
	Keyed 20
Housing Features	
Housing Features Circular Connector Shell Size	
Housing Features Circular Connector Shell Size Dimensions	20
Housing Features Circular Connector Shell Size Dimensions Wire Size	20
Housing Features Circular Connector Shell Size Dimensions Wire Size Usage Conditions	20 .14 – .25 mm², .14 – .25 mm²
Housing Features Circular Connector Shell Size Dimensions Wire Size Usage Conditions IP Water Sealing Level	20 .14 – .25 mm², .14 – .25 mm²
Housing Features Circular Connector Shell Size Dimensions Wire Size Usage Conditions IP Water Sealing Level IP Dust Sealing Level	20 .14 – .25 mm², .14 – .25 mm² 7
Housing Features Circular Connector Shell Size Dimensions Wire Size Usage Conditions IP Water Sealing Level IP Dust Sealing Level Operating Temperature Range	20 .14 – .25 mm², .14 – .25 mm² 7
Housing Features Circular Connector Shell Size Dimensions Wire Size Usage Conditions IP Water Sealing Level IP Dust Sealing Level Operating Temperature Range Operation/Application	20 .1425 mm², .1425 mm² 7 6 -40 - 85 °C[-40 - 185 °F]
Housing Features Circular Connector Shell Size Dimensions Wire Size Usage Conditions IP Water Sealing Level IP Dust Sealing Level Operating Temperature Range Operation/Application Circuit Application	20 .1425 mm², .1425 mm² 7 6 -40 - 85 °C[-40 - 185 °F] Signal
Housing Features Circular Connector Shell Size Dimensions Wire Size Usage Conditions IP Water Sealing Level IP Dust Sealing Level Operating Temperature Range Operation/Application Circuit Application Shielded	20 .1425 mm², .1425 mm² 7 6 -40 - 85 °C[-40 - 185 °F] Signal



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (.24% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









Also in the Series M12 Connector







Connector Hardware(12)







Customers Also Bought















Documents

Product Drawings
M12, FEMALE, A CODE, 12P, PG9 (AU)

English

CAD Files
3D PDF

3D

Customer View Model ENG_CVM_CVM_6-2271116-2_A.2d_dxf.zip

Cable-to-Cable, 12 Position, Sealable, Wire & Cable, Signal, Cable Mount (Free-Hanging), Reverse Gender, M12 Connector, Standard Circular Connectors



English

Customer View Model

ENG_CVM_CVM_6-2271116-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-2271116-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

Product Specifications

Product Specification

English