

**PRODUCTS**
[Rocker switches](#)
[Pushbutton switches](#)
[Toggle switches](#)
[Slide switches](#)
[Rotary switches](#)
[Foot switches](#)
[Tact and key switches](#)
**[Snap-action switches](#)**
[Micro-signal switches](#)
[ECO switches](#)
[Sensors](#)
[Systems and modules](#)
[Accessories](#)
[General information](#)
[Catalog request /  
download](#)
[PRODUCTS](#) ▶ [SNAP-ACTION SWITCHES](#)

## Snap-action switches

### SERIES 1019 - SINGLE-POLE SNAP-ACTION SWITCHES - TO 6 (2) A 250 V AC

[◀ Show previous product](#)
[Show next product ▶](#)

1019.0201

[Drawing](#)


Similar to original  
product

→ [Print data sheet](#)

Product number	1019.0201
Switching function	Normally open contact (SPNO)
Number of poles	1-pole
connections	PCB terminal, left
Mechanical life endurance	20E4
Rating IEC	6 (2) A 250 V AC 1E4
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Ambient temperature	-40 °C ... +85 °C
Flammability	UL 94 (socket, lever: V-0, actuator: V-2)
Glow wire test temperature	850 °C
Actuators and additional actuators	PA
Housing description	PA glass fiber-reinforced
Connection surface	external connection silver plated
Contact material	Ag
Contact distance	> 3 mm
Operating force	1.5 - 3 N
Difference travel max.	1.2 mm
Free position (FP) max.	4.7 mm
Operating position (OP)	2.4 ±0.6 mm
Permissible total travel position	0.5 mm
Approval marks	ENEC 10