

FP 0,8/ 20-MV-SH 8,65 - SMD male connector, shielded

1154120

<https://www.phoenixcontact.com/us/products/1154120>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



shielded SMD male connector, nominal current: 1.7 A, Test voltage: 500 V AC, number of positions: 20, pitch: 0.8 mm, color: black, contact surface: Au, contact connection type: Pin, mounting: SMD soldering

Your advantages

- Gold-plated contacts ensure transfer quality remains stable over the long term
- Reliable mechanical and electrical connections, thanks to the double-sided ScaleX contact system
- Robustness: ScaleX technology for high tolerance compensation and protection of contacts
- Flexible device design: various numbers of positions, designs, and stack heights with high wipe lengths

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1154120 |
| Packing unit | 250 pc |
| Minimum order quantity | 250 pc |
| Sales key | AA23 |
| Product key | AAWJDE |
| GTIN | 4063151154905 |
| Weight per piece (including packing) | 3.816 g |
| Weight per piece (excluding packing) | 3.8 g |
| Customs tariff number | 85366930 |
| Country of origin | CN |

FP 0,8/ 20-MV-SH 8,65 - SMD male connector, shielded



1154120

<https://www.phoenixcontact.com/us/products/1154120>

Technical data

Product properties

| | |
|---------------------------|-----------------------------|
| Product type | shielded SMD male connector |
| Product family | FP 0,8/...-MV-SH 8,65 |
| Number of positions | 20 |
| Pitch | 0.8 mm |
| Number of rows | 2 |
| Pin layout | Linear pad geometry |
| Electrical characteristic | shielded |

Data management status

| | |
|------------------|----|
| Article revision | 01 |
|------------------|----|

Electrical properties

| | |
|---------------------------|---|
| Nominal current I_N | 1.7 A IEC 60512-5-2:2002-02 (at 20°C 80-pos.) |
| Contact resistance | 25 mΩ |
| Test voltage | 500 V AC IEC 60512-4-1:2003 |
| Electrical characteristic | shielded |

Mounting

| | |
|---------------|---------------------|
| Mounting type | SMD soldering |
| Pin layout | Linear pad geometry |

Processing notes

| | |
|----------------------------------|------------------|
| Process | Reflow soldering |
| Moisture Sensitive Level | MSL 1 |
| Classification temperature T_c | 260 °C |

Material specifications

Material data - contact

| | |
|---|--|
| Note | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201 |
| Contact material | Cu alloy |
| Surface characteristics | Selective coating |
| Metal surface contact area (top layer) | Gold (Au) |
| Metal surface contact area (middle layer) | Nickel (Ni) |
| Metal surface soldering area (top layer) | Tin (Sn) |
| Metal surface soldering area (middle layer) | Nickel (Ni) |

Material data - housing

| | |
|----------------------------|--------------|
| Color (Housing) | black (9005) |
| Insulating material | LCP |
| Insulating material group | IIIb |
| CTI according to IEC 60112 | 150 |

FP 0,8/ 20-MV-SH 8,65 - SMD male connector, shielded



1154120

<https://www.phoenixcontact.com/us/products/1154120>

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Notes

| | |
|---------------------------------|--|
| Notes on operation | The permissible voltage during operation depends on the application, taking into consideration the air clearances and creepage distances within the scope of insulation requirements in accordance with IEC 60664-1. |
| Details for soldering processes | The items are suitable for assembly on both sides and for overhead soldering. |

Dimensions

| | |
|---------------------|----------|
| Dimensional drawing | |
| Pitch | 0.8 mm |
| Width [w] | 11.9 mm |
| Height [h] | 13.75 mm |
| Length [l] | 6.1 mm |
| Installed height | 13.15 mm |

Application

| | |
|--|---|
| Contact cover | 0.8 mm |
| Center offset | ± 0.7 mm in longitudinal and transverse direction |
| Stack height | 13.5 mm Tolerance: +1,5 mm (in combination with Range of articles:FP 0,8/...-FV-SH 4,85) |
| | 16.5 mm Tolerance: +1,5 mm (in combination with Range of articles:FP 0,8/...-FV-SH 7,85) |
| | 19.5 mm Tolerance: +1,5 mm (in combination with Range of articles:FP 0,8/...-FV 10,85) |
| | 19.5 mm Tolerance: +1,5 mm (in combination with Range of articles:FP 0,8/...-FV-SH 10,85) |
| Wipe length | 1.5 mm |
| Angular tolerance | ± 5 ° in longitudinal and transverse direction (when plugging in) |
| | ± 5 ° in longitudinal and transverse direction (when plugged in) |
| Axial offset in X direction (longitudinal) | ± 0.3 mm (Tolerance compensation when plugged in) |
| Axial offset in Y direction (transversal) | ± 0.3 mm (Tolerance compensation when plugged in) |

PCB design

| | |
|---------------|--------------|
| Pad geometry | 0.5 x 1.1 mm |
| Hole diameter | 0.75 mm |

Electrical tests

Thermal test | Test group C

| | |
|---------------|-----------------------|
| Specification | IEC 60512-5-2:2002-02 |
|---------------|-----------------------|

FP 0,8/ 20-MV-SH 8,65 - SMD male connector, shielded



1154120

<https://www.phoenixcontact.com/us/products/1154120>

| | |
|---|-----------------------|
| Tested number of positions | 80 |
| Insulation resistance | |
| Specification | IEC 60512-3-1:2002-02 |
| Insulation resistance, neighboring positions | ≥ 5 GΩ |
| Air clearances and creepage distances | |
| Insulating material group | IIIb |
| Minimum value for clearance and creepage distance | 0.25 mm |

Environmental and real-life conditions

Vibration test

| | |
|------------------------|--|
| Specification | IEC 60068-2-6:2007-12 |
| Frequency | 10 - 2000 - 10 Hz |
| Sweep speed | 1 octave/min |
| Amplitude | 1.5 mm (10 Hz ... 58 Hz) |
| Acceleration | 200 m/s ² (58 Hz ... 2000 Hz) |
| Test duration per axis | 2.5 h |
| Test directions | X-, Y- and Z-axis |

Durability test

| | |
|--|-----------------------------------|
| Specification | IEC 60512-9-1:2010-03 (following) |
| Contact resistance R ₁ | 25 mΩ |
| Contact resistance R ₂ | 25 mΩ |
| Insertion/withdrawal cycles | 500 |
| Insulation resistance, neighboring positions | ≥ 5 GΩ |

Shocks

| | |
|-----------------|-----------------------------------|
| Specification | IEC 60068-2-27:2008-02 |
| Pulse shape | Semi-sinusoidal |
| Acceleration | 490 m/s ² |
| Shock duration | 11 ms |
| Test directions | X-, Y- and Z-axis (pos. and neg.) |

Ambient conditions

| | |
|---|-------------------|
| Ambient temperature (operation) | -55 °C ... 125 °C |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Relative humidity (storage/transport) | 30 % ... 70 % |
| Ambient temperature (assembly) | -5 °C ... 100 °C |

Packaging specifications

FP 0,8/ 20-MV-SH 8,65 - SMD male connector, shielded



1154120

<https://www.phoenixcontact.com/us/products/1154120>

| | |
|-----------------------------|--|
| Dimensional drawing | |
| Type of packaging | 32 mm wide tape |
| [W] tape width | 32 mm |
| [W2] coil overall dimension | 330 mm |
| [A] coil diameter | 38.4 mm |
| Outer packaging type | Transparent-Bag |
| ESD level | (D) electrostatically conductive |
| Specification | DIN EN 61340-5-1 (VDE 0300-5-1): 2008-07 |

FP 0,8/ 20-MV-SH 8,65 - SMD male connector, shielded




1154120

<https://www.phoenixcontact.com/us/products/1154120>


Drawings

Diagram



Type: FP 0,8/...-MV-SH 8,65 with FP 0,8/...-FV-SH 7,85 – contacts

Diagram



Type: FP 0,8/...-MV-SH 8,65 with FP 0,8/...-FV-SH 10,85 - shroud


FP 0,8/ 20-MV-SH 8,65 - SMD male connector, shielded



1154120


<https://www.phoenixcontact.com/us/products/1154120>

Diagram



Type: FP 0,8/...-MV-SH 8,65 with FP 0,8/...-FV-SH 7,85 - shroud

Diagram



Type: FP 0,8/...-MV-SH 8,65 with FP 0,8/...-FV-SH 10,85 - contacts

FP 0,8/ 20-MV-SH 8,65 - SMD male connector, shielded



1154120

<https://www.phoenixcontact.com/us/products/1154120>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1154120>



cULus Recognized

Approval ID: E118976-20190703

FP 0,8/ 20-MV-SH 8,65 - SMD male connector, shielded



1154120

<https://www.phoenixcontact.com/us/products/1154120>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27460201 |
| ECLASS-12.0 | 27460201 |
| ECLASS-13.0 | 27460201 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002637 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

FP 0,8/ 20-MV-SH 8,65 - SMD male connector, shielded



1154120

<https://www.phoenixcontact.com/us/products/1154120>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

FP 0,8/ 20-MV-SH 8,65 - SMD male connector, shielded

1154120


<https://www.phoenixcontact.com/us/products/1154120>

Mandatory accessories

FP 0,8/ 20-FH-SH - SMD female connector shielded

1053616

<https://www.phoenixcontact.com/us/products/1053616>



Shielded SMD female connector, nominal current: 1.7 A, Test voltage: 500 V AC, number of positions: 20, pitch: 0.8 mm, color: black, contact surface: Au, contact connection type: Socket, mounting: SMD soldering

FP 0,8/ 20-FV-SH 10,85 - SMD female connectors

1154032

<https://www.phoenixcontact.com/us/products/1154032>



Shielded SMD female connector, nominal current: 1.7 A, Test voltage: 500 V AC, number of positions: 20, pitch: 0.8 mm, color: black, contact surface: Au, contact connection type: Socket, mounting: SMD soldering

FP 0,8/ 20-MV-SH 8,65 - SMD male connector, shielded

1154120

<https://www.phoenixcontact.com/us/products/1154120>

FP 0,8/ 20-FV-SH 4,85 - SMD female connector shielded

1053612

<https://www.phoenixcontact.com/us/products/1053612>



Shielded SMD female connector, nominal current: 1.7 A, Test voltage: 500 V AC, number of positions: 20, pitch: 0.8 mm, color: black, contact surface: Au, contact connection type: Socket, mounting: SMD soldering

FP 0,8/ 20-FV-SH 7,85 - SMD female connector shielded

1053614

<https://www.phoenixcontact.com/us/products/1053614>



Shielded SMD female connector, nominal current: 1.7 A, Test voltage: 500 V AC, number of positions: 20, pitch: 0.8 mm, color: black, contact surface: Au, contact connection type: Socket, mounting: SMD soldering

Accessories

FP 0,8/ 20-MV-SH 8,65 - SMD male connector, shielded



1154120

<https://www.phoenixcontact.com/us/products/1154120>

FP 0,8/ 20-FV-SH 4,85 - SMD female connector shielded

1053612

<https://www.phoenixcontact.com/us/products/1053612>



Shielded SMD female connector, nominal current: 1.7 A, Test voltage: 500 V AC, number of positions: 20, pitch: 0.8 mm, color: black, contact surface: Au, contact connection type: Socket, mounting: SMD soldering

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com