

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2024.12.6	阿树

Specifications:
规格:
Voltage rating:50V AC/DC
额定电压: 50V AC/DC
Current rating:0.8A AC/DC
额定电流: 0.8A AC/DC
Withstanding voltage:250V AC/minute
耐受电压: 250V AC/分钟
Temperature range:-40℃-+125℃
温度范围: -40℃-+125℃

PART NO.:
X1004 W V S-2xXX-9T V01
① ② ③ ④ ⑤ ⑥ ⑦
①Series No
②Category:W-Wafer
③Welding Board Angle:V-Stright 180°
④Welding way :S-SMT
⑤ Row No.Pin No.: 2xXX-2x10~2x25Pin
⑥Material:9T-PA9T 94V-0
⑦Plating Category:V01-Gold Flash

PIN	A	B	C	D
2X10P	9.00	12.30	10.45	11.25
2X15P	14.00	17.30	15.45	16.25
2X20P	19.00	22.30	20.45	21.25
2X25P	24.00	27.30	25.45	26.25

X1004WVS-2xXX-9TV01	PA9T UL 94V-0	Brass	X1004T-A
PART NO	Material	Material(Pin)	Suitable XKB Terminal

AuGLAR	±5°		DESIGN	阿树	VIEW: 	MODEL TYPE: 2.54mm Crimp Style Connector		
X.	±0.40		CHECKED		UNIT: mm/in	PART NO.: X1004WVS-2xXX-9TV01		
X.x	±0.30		APPROVED		SIZE: A4	DWG NO.:		
X.xx	±0.20							
X.xxx	±0.15							
UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED				SCALE N/A	PAGE 1/1	REVISION A1
www.xk-dg.cn								

