

Search within category **GO**

BUY NOW

DESIGN / INSTALL



LCMA6-8-C

One-hole, metric conductor, standard barrel with window lug, 4-6mm² wire, M8 stud hole.

Specs **Packaging Details** **Documents** [★ Add to Favorites](#) [Add to BOM](#)

Material	Tin-Plated Copper
Overall Length (mm)	30.5
Tongue Thickness (mm)	1
Standards Met	Meets EN 61238-1:2003/IEC 61238-1:2003 Class B WITH Class 2r Wire
Conductor Material	Copper
Product Type	Tin-Plated Copper Compression Connectors - Metric Lugs
Barrel Type	Standard Barrel Length with Inspection Window
Copper Conductor Size Class 2 (mm ²)	6.0
Copper Conductor Size Class 5F (mm ²)	NA
Copper Conductor Size Class 6F (mm ²)	NA
Barrel Inside Diameter (mm)	3.8
Barrel Length (mm)	11.0
Palm Width (mm)	13.0
Stud Set Back (mm)	8.0
Wrench Clearance (mm)	8.0
Panduit Die Index Number	P10
Wire Strip Length (mm)	11.0
American Bureau Shipping Approved	Yes
CE Compliant	Yes
CSA Certified	C22.2 No. 65-13
Tin-Plating Meets ASTM B545-97, Class C	320µ-in (8 µm)
UL Listed	486A-486B File #E52164
UL and CSA Temperature Rating	90°C
UL and CSA Voltage Rating	35kV
Part Number Series	LCMA
Barrel Style	Standard
Part Features	Tin plated to inhibit corrosion,color coded barrel,inspection window.
Technical Information	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V
RoHS Compliancy Status	Compliant

Min. Order Qty.

1

Sub Brand

Pan-Lug

[LEGAL INFORMATION](#) | [PRIVACY POLICY](#) | [CONTACT US](#) | [SITE MAP](#) | [WHERE TO BUY](#) | [JOBS](#) | [UNSUBSCRIBE](#)