

#### Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

## NetCommander USB Server Interface Unit (SIU) -Single

### MODEL NUMBER: B078-101-USB-1



#### Description

The Tripp Lite NetCommander USB Server Interface Unit (SIU) connects to the HD15 port and USB port on a computer/server, and converts them to a single RJ45 connector. Ordinary Cat5e patch cables can then be used to connect the server to the switch ports on a Tripp Lite B070 / B072-Series NetCommander Cat5 KVM switch. Use of Cat5e cables frees up space in the installation that would ordinarily be filled by traditional, thicker KVM cables. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

#### Features

- Needed to connect a USB Server to a B070 / B072-Series NetCommander KVM switch via Cat5e cable
- Eliminates the need for thicker, heavier KVM cables
- Compact, lightweight design
- Plug and Play; no software required
- No power supply required
- Allows a Server/CPU to be located up to 100ft away from the KVM switch
- To convert DisplayPort or HDMI computers to VGA, use Tripp Lite adapters P134-06N-VGA-V2 or P131-06N
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule Purchases

# **Specifications**

## Highlights

- Needed to connect a USB Server to a B070 / B072-Series NetCommander KVM switch via Cat5e cable
- Easy to install; no software needed
- No power supply required
- Allows a recommended maximum distance of 100ft from KVM to computer/server via Cat5e cable
- Compact and lightweight design

#### **System Requirements**

- Server or CPU with a HD15 port and a USB port
- A B070 / B072-Series
  NetCommander Cat5 KVM
  Switch
- Cat5e/6 cable; up to 100ft
- To convert DisplayPort or HDMI computers to VGA, use Tripp Lite adapters P134-06N-VGA-V2 or P131-06N

#### Package Includes

(x1) B078-101-USB-1 USB
 Server Interface Unit (SIU)

OVERVIEW	
Accessories Type	Server Interface Unit



INPUT		
Bus Powered	Yes	
Product Length (ft.)	1.3	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	GREEN (RECEIVING POWER); ORANGE (SELECTED AS ACTIVE PORT)	
PHYSICAL		
Shipping Dimensions (hwd / in.)	1.1 x 5.9 x 4.7	
Shipping Weight (lbs.)	0.2	
Unit Weight (lbs.)	0.18	
Unit Weight (kg)	0.08	
Material of Construction	ABS	
Color	Gray	
CONNECTIONS		
Side A - Connector 1	HD15 (MALE)	
Side A - Connector 2	USB A (MALE)	
Side B - Connector 1	RJ45 (FEMALE)	
Computer Keyboard and Mouse Interface	USB	
Computer Monitor Interface	VGA	
FEATURES & SPECIFICATIONS		
Driver Required	No	
Recommended Category Cable	N105 - SERIES CAT5E SHIELDED CABLES	
CERTIFICATIONS		
Certifications	Tested to EN55022/EN55024, CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies