

4-Port 4K HDMI Splitter for Ultra-HD (4Kx2K) Video and Audio - 4096 x 2160 @ 30Hz

MODEL NUMBER: **B118-004-UHD**



Description

Tripp Lite's B118-004-UHD HDMI Splitter allows the 4K2K digital signal from a Blu-Ray player or other HDMI device to be displayed on up to four HDMI displays, or, connect a DVI-D Single Link display using an HDMI to DVI adapter, such as Tripp Lite's P566-Series cables. Installation is quick and simple, with no software or drivers to install. Locate your HDMI source up to 16.4 ft. (5 m.) from the splitter, and the splitter up to 16 ft. (5 m.) from a display, for a max distance of 23 ft. (7 m.) between splitter and display. Supports Full 3D and video resolutions up to both 4096 x 2160 and 3840 x 2160 (4K x 2K) @ 30Hz. High Speed HDMI and 3D compliant, with support for 36-bit Deep Color (12-bits per channel). Supports DTS-HD, Dolby True HD, Dolby Digital Plus, and LPCM 7.1 Channel Surround Sound audio. HDCP and EDID compliant.

Features

- Simultaneously transmit the video and audio from an HDMI source to multiple HDMI monitors
- Supports Full 3D and video resolutions up to both 4096 x 2160 and 3840 x 2160 (4K x 2K) @ 30Hz
- Supports 36-bit Deep Color (12-bits per channel)
- Supports DTS-HD, Dolby True HD, Dolby Digital Plus and LPCM 7.1 Channel Surround Sound audio
- Supports video amplifier bandwidth of 340MHz / 3.4Gbps per channel (10.2Gbps total)
- HDCP and EDID compatible
- Plug and play; no software or drivers required
- Supports Lip Sync pass-through
- Supports xvYCC and x.vColor
- Supports the use of DVI sources and displays with the use of an optional DVI to HDMI adapter (sold separately)
- Supports a maximum distance of 16.4 ft. (5 m) from source to splitter, and 23 ft. (7 m) from splitter to display, for a total of up to 39.4 ft. (12 m)

Highlights

- Supports Full 3D and video resolutions up to both 4096 x 2160 and 3840 x 2160 (4K x 2K) @ 30Hz
- Supports DTS-HD, Dolby True HD, Dolby Digital Plus and LPCM 7.1 Channel Surround Sound audio
- Plug and play; no software or drivers required

Package Includes

- UHD 4Kx2K HDMI 4-port Splitter
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 3A, 4 ft.)
- Owner's Manual



Specifications

| MODEL TEXT | |
|-------------------------------------|--|
| What Does This Product Do? | Transmit a 4Kx2K HDMI signal from a single source to four displays |
| OVERVIEW | |
| AC Adapter | Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 3A, 4 ft. |
| CONNECTIONS | |
| Ports | 4 |
| Side A - Connector 1 | HDMI (FEMALE) |
| Side B - Connector 1 | (4) HDMI (FEMALE) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>