



Circuit breaker 10kA, 3-pole, C, 0.5 A according to UL 489-480Y/277V

Model	
product brand name	SENTRON
product designation	Miniature circuit breakers
design of the product	Miniature circuit-breaker 5SJ4
General technical data	
number of poles	3
number of poles / note	3P
tripping characteristic class	C
mechanical service life (switching cycles) / typical	20 000
installation environment regarding EMC	Suitable for environment B (immunity to interference not applicable)
reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	F
overvoltage category	3
degree of pollution	3
Voltage	
insulation voltage / at AC / rated value	440 V
Supply voltage	
type of voltage	AC/DC
operational current / at AC / rated value	0.5 A
supply voltage / at AC / rated value	400 V
operating voltage	
<ul style="list-style-type: none"> <li>• at AC / acc. to UL 489 and CSA C22.2 No. 5-02 / maximum</li> </ul>	277 V
<ul style="list-style-type: none"> <li>• at DC / rated value / maximum</li> </ul>	60 V
<ul style="list-style-type: none"> <li>• at DC / single channel / acc. to UL 489 and CSA C22.2 No. 5-02 / maximum</li> </ul>	60 V
<ul style="list-style-type: none"> <li>• at DC / 2-channel / acc. to UL 489 and CSA C22.2 No. 5-02 / maximum</li> </ul>	125 V
supply voltage frequency	
<ul style="list-style-type: none"> <li>• rated value</li> </ul>	50 Hz
Protection class	
protection class IP	IP20, with connected conductors, IP 40 in the handle range
Switching capacity	
switching capacity current	
<ul style="list-style-type: none"> <li>• acc. to EN 60898 / rated value</li> </ul>	10 kA
<ul style="list-style-type: none"> <li>• acc. to IEC 60947-2 / rated value</li> </ul>	15 kA
Dissipation	
power loss [W] / for rated value of the current / at AC / in	1.2 W

hot operating state / per pole	
<b>Main circuit</b>	
type of voltage supply / at AC / acc. to UL 489 and CSA C22.2 No. 5-02	480/277
suitability for operation	Mechanical engineering / industry
<b>Product details</b>	
product function / neutral conductor switching	No
product feature / touch protection	Yes
product component	
• tunnel terminals top	No
• tunnel terminals bottom	No
• combined terminal top	Yes
• combined terminal bottom	Yes
product feature	
• halogen-free	Yes
• sealable	Yes
• silicon-free	Yes
product extension / installable / supplementary devices	Yes
<b>Product function</b>	
product function / note	Terminal tightening torque for Cu, 60/75°C; 3.5Nm/31lb.in
<b>Short circuit</b>	
breaking capacity short-circuit current (I <sub>cn</sub> ) / at AC / acc. to UL 1077 and CSA C22.2 No.235	10 kA
<b>Connections</b>	
connectable conductor cross-section / finely stranded / with core end processing	
• minimum	1.5 mm <sup>2</sup>
• maximum	25 mm <sup>2</sup>
position / of power supply cord	Any
<b>Mechanical Design</b>	
height	121 mm
width	54 mm
depth	76 mm
installation depth	70 mm
number of modular width units	3
fastening method	on standard mounting rail
mounting position	any
net weight	501 g
<b>Environmental conditions</b>	
influence of the surrounding temperature	max. 95% humidity
vibration resistance	50 m/s <sup>2</sup> at 25 to 150Hz and 60m/s <sup>2</sup> at 35Hz (4sec)
vibration resistance / acc. to IEC 60068-2-6	50 m/s <sup>2</sup> at 25 to 150Hz and 60m/s <sup>2</sup> at 35Hz (4sec)
ambient temperature	
• minimum	-25 °C
• maximum	55 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	75 °C
<b>Certificates</b>	
reference code	
• acc. to DIN EN 61346-2	F
• acc. to IEC 81346-2	F
<b>General Product Approval</b>	<b>Declaration of Conformity</b>



## Test Certificates

[Special Test Certificate](#)

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SJ4305-7HG42>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5SJ4305-7HG42>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SJ4305-7HG42](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SJ4305-7HG42)

**Tender specifications**

<http://www.siemens.com/specifications>

