

## SKINDICHT® MR-M ATEX

SKINDICHT® MR-M ATEX, reducer, enables the use of cable glands with smaller connection threads than the existing threaded holes



### Benefits

Enables the use of cable glands with smaller connection threads than the existing threaded holes  
With guide slot for O-ring  
Assembling with a wrench

### Application range

Equipment group II / category 2G+1D  
Devices, machines and apparatus  
For mobile applications in offshore and marine industries  
Chemical and petrochemical industry

### Design

Metric connection thread according to DIN EN 60423  
Basis for technical information DIN IEC 62444

### Technical Data

Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: Cable gland
Certifications:	CE 0637 Ex II 2G Ex eb IIC Ex II 1D Ex ta IIIC IECEx IBE 13.0028X DIN EN 60079-0DIN EN 60079-7DIN EN 60079-31
Material:	Body: Nickel-plated brass O-ring: NBR
Temperature range:	-30°C to +90°C

## SKINDICHT® MR-M ATEX

### Note

Photographs are not to scale and do not represent detailed images of the respective products.

\* Prices are net prices without VAT and surcharges. Sale to business customers only.

**SKINDICHT® MR-M ATEX**

Article number	Thread, male M1	Thread, inner M2	Overall height (mm)	Thread length, D (mm)	Outer Ø (mm)
SKINDICHT® MR-M ATEX					
52104570	16 x 1.5	12 x 1.5	10.5	5	19
52104571	20 x 1.5	16 x 1.5	13	6	24.5
52104572	25 x 1.5	20 x 1.5	15	7	30.1
52104573	32 x 1.5	25 x 1.5	16.5	8	37.2
52104574	40 x 1.5	32 x 1.5	16.5	8	45.6
52104575	50 x 1.5	40 x 1.5	19.5	10	55.3
52104576	63 x 1.5	50 x 1.5	18.5	8.5	71.3

Last Update (22.03.2017)

©2017 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.  
PN 0456 / 02\_03.16