



Timing Relay, Type JCK, plug In, on delay, adjustable time, 0.1 to 10 seconds, 10A, 240 VAC, 24 VAC/DC

9050JCK11V14

Main

product range	9050JCK	
product type	Timer	
timing mode	On-delay	
timing range	0.110 s	
supply voltage	24 V AC/DC	

Complementary

power consumption	2 VA
current rating	10 A
switch function	DPDT
contact composition	2 NO + 2 NC
contact material	Silver nickel
maximum switching voltage	240 V AC
mounting type	Socket
number of pins	8
shape of pins	Tubular
for use with	8501NR52 8501NR51

Environment

certifications	CE UL listed UL recognized
ambient temperature range - operational	-27.865.6 °C (-18150 °F)
Height	2.4 in (61 mm)
Width	1.7 in (43 mm)
Depth	4.09 in (104 mm)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.400 in (6.096 cm)
Package 1 Width	2.0000000000 in (5.08 cm)

Package 1 Length	4.300 in (10.922 cm)	
Package 1 Weight	3.840 oz (108.862 g)	
Unit Type of Package 2	CAR	
Number of Units in Package 2	20	
Package 2 Height	4.50 in (11.43 cm)	
Package 2 Width	10.000000000 in (25.4 cm)	
Package 2 Length	11.0000000000 in (27.94 cm)	
Package 2 Weight	5.501 lb(US) (2.495 kg)	

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information