

Description

The uses advanced SGT technology to provide excellent RDS(ON), low gate charge and operation with gate voltages as low as 4.5V. This device is suitable for use as a Battery protection or in other Switching application.


Application

- Consumer electronic power supply
- Motor control
- Synchronous-rectification
- Isolated DC

Product Summary

BVDSS	RDSON	ID
100V	13.8mΩ	40A

TO-252 Pin Configuration



Absolute Maximum Ratings (TC=25°C unless otherwise noted)

Symbol	Parameter	Rating	Units
VDS	Drain source voltage	100	V
VGS	Gate source voltage	±20	V
ID	Continuous drain current ₁₎	TC=25 °C 40	A
ID, pulse	Pulsed drain current ₂₎	TC=25 °C 120	A
P _D	Power dissipation ₃₎	TC=25 °C 71	W
EAS	Single pulsed avalanche energy ₅₎	57	mJ
T _{stg} , T _j	Operation and storage temperature	-55 to 150	°C
R _{θJC}	Thermal resistance, junction-case	1.76	°C/W
R _{θJA}	Thermal resistance, junction-ambient ₄₎	62	°C/W

Electrical Characteristics (T_c=25°C unless otherwise noted)

Symbol	Parameter	Test condition	Min.	Typ.	Max.	Unit
BVDSS	Drain-source breakdown voltage	V _{GS} =0 V, I _D =250 μA	100	107	-	V
VGS(th)	Gate threshold voltage	V _{DS} =V _{GS} , I _D =250 μA	1.2	1.5	2.5	V
RDS(ON)	Drain-source on-state resistance	V _{GS} =10 V, I _D =10 A	-	13.8	20.0	mΩ
RDS(ON)	Drain-source on-state resistance	V _{GS} =4.5 V, I _D =7 A	-	17.4	26.0	mΩ
IGSS	Gate-source leakage current	V _{GS} =±20 V	-	-	±100	nA
IDSS	Drain-source leakage current	V _{DS} =100 V, V _{GS} =0 V	-	-	1	μA
Ciss	Input capacitance	V _{GS} =0 V, V _{DS} =50 V, f=100 kHz	-	1003.9	-	pF
Coss	Output capacitance		-	185.4	-	pF
Crss	Reverse transfer capacitance		-	9.8	-	pF
td(on)	Turn-on delay time	V _{GS} =10 V, V _{DS} =50 V, R _G =10 Ω, I _D =5 A	-	16.6	-	ns
t _r	Rise time		-	3.8	-	ns
td(off)	Turn-off delay time		-	75.5	-	ns
t _f	Fall time		-	46	-	ns
Q _g	Total gate charge	I _D =5 A, V _{DS} =50V, V _{GS} =10V	-	16.2	-	nc
Q _{gs}	Gate-source charge		-	2.8	-	nc
Q _{gd}	Gate-drain charge		-	4.1	-	nc
V _{plateau}	Gate plateau voltage		-	3	-	V
I _s	Diode forward current	V _{GS} <V _{th}	-	30	-	A
ISP	Pulsed source current		-	90	-	A
t _{rr}	Reverse recovery time	I _S =1A, di/dt=100 A/μs	49	-	-	ns
Q _{rr}	Reverse recovery charge		61.8	-	-	nc
I _{rrm}	Peak reverse recovery current		2.4	-	-	A

Note :

- 1、 Calculated continuous current based on maximum allowable junction temperature.
- 2、 Repetitive rating; pulse width limited by max. junction temperature.
- 3、 Pd is based on max. junction temperature, using junction-case thermal resistance.
- 4、 The value of R_{θja} is measured with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with T_a=25 °C.
- 5、 V_{DD}=50 V, R_G=25 Ω, L=0.3 mH, starting T_j=25 °C.

Typical Characteristics




Figure 1, Typ. output characteristics




Figure 2, Typ. transfer characteristics




Figure 3, Typ. capacitances




Figure 4, Typ. gate charge




Figure 5, Drain-source breakdown voltage




Figure 6, Drain-source on-state resistance




Figure 7, Forward characteristic of body diode




Figure 8, Drain-source on-state resistance




Figure 9, Drain current




Figure 10, Safe operation area $T_C=25\text{ }^\circ\text{C}$




Fig11. Normalized Maximum Transient Thermal Impedance



Attention

- 1, Any and all Winsok power products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your Winsok power representative nearest you before using any Winsok power products described or contained herein in such applications.
- 2, Winsok power assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all Winsok power products described or contained herein.
- 3, Specifications of any and all Winsok power products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- 4, Winsok power Semiconductor CO., LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- 5, In the event that any or all Winsok power products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- 6, No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of Winsok power Semiconductor CO., LTD.
- 7, Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. Winsok power believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- 8, Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the Winsok power product that you intend to use.
- 9, this catalog provides information as of Sep. 2014. Specifications and information herein are subject to change without notice.