





1. Rating:

5 Amps with resistive load at 120 VAC or 28 VDC 2 Amps with resistive load at 250 VAC

Contact Material

Contact Surface: Coin Silver

Center Terminal Body: Coin Silver or silver plated brass

4. Electrical Life: 50,000 make-and-break cycles at full load 5. Contact Resistance:

Body: Brass, silver plated

Contact Surface: Brass, silver plated

10 milliohm maximum

Initial at 2 to 4 VDC 100 milliamp

Operating Temperature: -30°C to 85°C
 Toggle Handle: Brass, chrome plated

9. Housing: Stainless Steel 8. Bushing: Brass, nickel plated

- 10. UL Listed
- 11. Includes: Hex nut, lock washer and locking ring12. Insulation Resistance: 1000 Megaohms minimum13. Dielectric Strength: 1000 V RMS at sea level

Part Number Table

Toggle Switch , Spot SPC21274

0.078 (1.98)

0.047 (1.19)

0.031 (0.79)

0.378 (9.60)

윽

Dimensions : Inches (mm)

0.156 (3.96)

(1.91) maximum **EPOXY SEAL**

0.065 (1.65)

- Ø.469 (11.91)

/(3.81)Ø.150

7(11.91)

PANEL MOUNTING

TERMINATION

(ON) - NONE- (ON)

Schematic 2 Com.

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION
ALL STATEMENTS AND TECHNICAL INFORMATION AND/
HEREIN ARE BASED UPON INFORMATION AND/
BELIEVE TO BE ACCURATE AND RELIABLE. SINI
CONDITIONS OF USE ARE BEYOND OUR CONTIUSER SHALL DETERMINE THE SUITABILITY OF THFOR THE INTENDED USE AND ASSUME ALL RIS
LIABILITY WHATSOEVER IN CONNECTION THEREW

	REWITH.	RISK AND	ONTROL, THE	SINCE		
	PURPOSES ONLY,		DIMENSIONS ARE	SPECIFIED,	UNLESS OTHERWISE	TOLERANCES:
XXX	APPROVED BY:		MRE	CHECKED BY:	AMU	DRAWN BY:
16-08-10	DAIE:	7	05-08-10	DATE:	02-08-10	DATE:
	SCALE: NTS		<u>×</u>	SIZE DWG. NO.		DRAWING TITLE:
U.O.M.: INCHES [mm]	INCHES		× × ×	ELEC	loggle Switch , Spot	
SHEET: 1 O	SHEET: 1 OI		50N285	CTRONIC FILE	-	•