



Series 80 Mighty Mouse Standard Series Discrete Connector Offerings

The Series 80 Mighty Mouse Connector is designed for high-reliability commercial and aerospace/defense interconnect applications that require both robust environmental/EMI performance and reduced size and weight. The Series 80 Mighty Mouse Connector offers comparable performance to MIL-DTL-38999 Series interconnects with up to 71% weight and 52% size savings for similar contact layouts. The six versions of the product offer a variety of styles and features to suit just about any application.

Series 800







Series 801



Description	Original Mighty Mouse with UNF Threads	Double-Start ACME Thread
Notes	A general purpose connector for high-speed Ethernet switches, tactical equipment and instrumentation.	More rugged keys and threads compared to Series 800. Faster mating, slightly larger than Series 800.
Number of Contacts	1 to 37	1 to 130
Coupling	Threaded Coupling with 4 ½ Turns to Full Mate	Threaded Coupling with 1 ½ Turns to Full Mate
Water Immersion, Mated	MIL-STD-810 Method 512 1 Meter for 1 Hour	MIL-STD-810 Method 512 1 Meter for 1 Hour
EMI Shielding	Good	Good
Vibration and Shock	37 g's Random Vibration; 300 g's Shock	37 g's Random Vibration; 300 g's Shock
Mating Cycles	2000 Cycles	2000 Cycles
Electrical Performance	#12: 23 Amp, 1800 VAC #16: 13 Amp, 1800 VAC #20HD: 7.5 Amp, 1000 VAC #23: 5 Amp, 750 VAC	#12: 23 Amp, 1800 VAC #16: 13 Amp, 1800 VAC #20HD: 7.5 Amp, 1000 VAC #23: 5 Amp, 750 VAC
Proven Performance Applications	Commercial air frame sensors; UAV telemetry; Tactical computers; field radios	Military air frame; Dismounted soldier; Tactical ground weaponry; Avionic (FLIR) systems

**Series 80 Mighty Mouse
Standard Series
Discrete Connector Offerings**



Series 802	Series 803	Series 804	Series 805
			
AquaMouse™ 3500 PSI	Bayonet	Push-Pull	Triple-Start ACME Thread
<p>Rugged stainless steel, resists chemicals. For geophysical and underwater applications.</p>	<p>Quick-mating, light duty, general purpose. Not rated for immersion. 50 milliohms shell-to-shell resistance.</p>	<p>Breakaway connector for headsets and tactical equipment. Gold-plated spring for long mating life and superior EMI shielding.</p>	<p>“Clicker” ratchet mechanism and ground spring for military airframes and avionics boxes. Fast-mating, D38999 equivalent.</p>
1 to 130	1 to 55	1 to 55	1 to 130
Threaded Coupling with UN Threads	Push-to-Mate, ¼ Turn to Lock	Quick-Disconnect	One Full Turn for Full Mate
1000 Feet Immersion in Salt Water	Splashproof	MIL-STD-810 Method 512 1 Meter for 1 Hour	MIL-STD-810 Method 512 1 Meter for 1 Hour
Good	Fair	Very Good	Excellent
37 g's Random Vibration; 300 g's Shock	37 g's Random Vibration; 300 g's Shock	37 g's Random Vibration; 300 g's Shock	37 g's Random Vibration; 300 g's Shock
2000 Cycles	250 Cycles Aluminum 2000 Cycles SST	2000 Cycles Aluminum 2000 Cycles SST	500 Cycles
#12: 23 Amp, 1800 VAC #16: 13 Amp, 1800 VAC #20HD: 7.5 Amp, 1000 VAC #23: 5 Amp, 750 VAC	#12: 23 Amp, 1800 VAC #16: 13 Amp, 1800 VAC #20HD: 7.5 Amp, 1000 VAC #23: 5 Amp, 750 VAC	#12: 23 Amp, 1800 VAC #16: 13 Amp, 1800 VAC #20HD: 7.5 Amp, 1000 VAC #23: 5 Amp, 750 VAC	#12: 23 Amp, 1800 VAC #16: 13 Amp, 1800 VAC #20HD: 7.5 Amp, 1000 VAC #23: 5 Amp, 750 VAC
Pipe line inspection equipment; Well logging; Amphibious vehicles; Unmanned submersibles	Soldier system radios; Autosport diagnostics; Airborne surveillance; Communication systems	Helmet breakaway connector; QDC battery; Missile applications; Weapon interconnects	Military air frame; Joint Strike Fighter

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Glenair:

[805-005-07NF9-10PA](#) [805-011-07M11-19SB](#) [805-011-07M11-19SA](#) [801-023-07M6-7PB](#) [805-005-07M10-2PA](#) [805-005-07NF11-19PB](#) [805-005-07NF18-55PA](#) [805-017-07M11-19SA](#) [805-017-07M11-201SB](#) [803-002-06M14-55PN](#) [801-023-07M6-7SA](#) [801-017M13-37PA](#) [801-017M13-37SA](#) [801-023-07M6-4SA](#) [805-005-07M12-26SA](#) [805-005-07NF8-7EB](#) [805-005-07ZN19-85SA](#) [801-023-07M7-10SA](#) [803-001-06M12-37SN](#) [801-023-07M5-3PA](#) [805-011-07M8-4PA](#) [805-005-07NF15-37PA](#) [801-017M10-26PA](#) [801-023-07M6-4PA](#) [801-023-07M6-7PA](#) [801-023-07M7-10PA](#) [801-023-07M8-13PA](#) [801-023-07NF6-7SA](#) [801-023-07ZNU5-3PA](#) [801-023-07ZNU5-3PB](#) [801-023-07ZNU5-3SB](#) [803-003-07ZNU10-26PN](#) [805-005-02M10-13PA](#) [805-005-02M10-13SA](#) [805-005-02M11-19PA](#) [805-005-02M11-19SA](#) [805-005-02M12-26PA](#) [805-005-02M12-26SA](#) [805-005-02M15-37PA](#) [805-005-02M15-37SA](#) [805-005-02M15-7EA](#) [805-005-02M15-7FA](#) [805-005-02M18-55PA](#) [805-005-02M18-55SA](#) [805-005-02M19-85PA](#) [805-005-02M19-85SA](#) [805-005-02M8-4PA](#) [805-005-02M8-4SA](#) [805-005-02M8-7PA](#) [805-005-02M8-7SA](#) [805-005-02M9-10PA](#) [805-005-02M9-10SA](#) [805-005-07M10-13PA](#) [805-005-07M10-13SA](#) [805-005-07M11-19PA](#) [805-005-07M11-19SA](#) [805-005-07M12-26PA](#) [805-005-07M15-37PA](#) [805-005-07M15-37SA](#) [805-005-07M15-37SB](#) [805-005-07M15-7PA](#) [805-005-07M18-55PA](#) [805-005-07M18-55SA](#) [805-005-07M19-85PA](#) [805-005-07M19-85SA](#) [805-005-07M8-4PA](#) [805-005-07M8-4SA](#) [805-005-07M8-7PA](#) [805-005-07M8-7SA](#) [805-005-07M9-10PA](#) [805-005-07M9-10SA](#) [805-005-07NF10-13SA](#) [805-005-07NF11-19PA](#) [805-005-07NF11-19SA](#) [805-005-07NF11-4EA](#) [805-005-07NF12-26SA](#) [805-005-07NF19-85PA](#) [805-005-07NF8-4FA](#) [805-005-07NF8-4PA](#) [805-005-07NF8-4SA](#) [805-005-07NF8-7EA](#) [805-005-07NF8-7PA](#) [805-005-07NF8-7SA](#) [805-005-07NF8-7SB](#) [805-005-07NF9-10SA](#) [805-005-07NF9-10SB](#) [805-005-07Z111-19PA](#) [805-006-02Z111-19PA](#) [805-006-07Z111-19CA](#) [805-006-07Z19-10CA](#) [805-006-07Z19-10CB](#) [805-011-07MT10-13PA](#) [805-011-07M11-19SC](#) [801-075-07M8-13SA](#) [801-023-07ZN8-13SA](#) [801-023-07NF7-10PB](#) [801-023-07ZN8-13SB](#) [801-023-07M9-19PC](#) [801-02307ZNU7-10SA](#) [801-023-07M6-4SA-501](#)