

PACT MCR-V2-6015-85-1000-1A-1 - Current transformer



2905886

<https://www.phoenixcontact.com/us/products/2905886>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Window-type current transformer, 1000 A AC primary current; 1 A AC secondary current; accuracy class 1; 2.5 VA rated power

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 2905886 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Product key | CK4A11 |
| GTIN | 4055626004877 |
| Weight per piece (including packing) | 297.9 g |
| Weight per piece (excluding packing) | 250 g |
| Country of origin | DE |

PACT MCR-V2-6015-85-1000-1A-1 - Current transformer



2905886

<https://www.phoenixcontact.com/us/products/2905886>

Technical data

Product properties

| | |
|--------------|---------------------|
| Product type | Current transformer |
|--------------|---------------------|

Electrical properties

| | |
|--------------------------|--------------------------------|
| Rated insulation voltage | 1 kV (Phase/neutral conductor) |
|--------------------------|--------------------------------|

General

| | |
|-------------------|---------------------------------|
| Can be calibrated | no |
| Converter type | Window-type current transformer |

Input data

Current transformers

| | |
|----------------------------------|----------------------------------|
| Rated power | 2.5 VA |
| Thermal rated short-time current | $I_{th} = 60 * I_n$ |
| Thermal rated continuous current | $I_d = 1.2 * I_n$ |
| Rated surge current | $I_{dyn} = 2.5 * I_{th}$ |
| Rated frequency f_n | 50 Hz 60 Hz |
| Primary rated current I_{pn} | 0 A ... 1000 A |
| Primary rated current range | 1 A ... 4000 A (depends on type) |
| Can be calibrated | no |
| Converter type | Window-type current transformer |

Output data

Signal

| | |
|----------------------------------|--------|
| Secondary rated current I_{sn} | 1 A AC |
| Surge current limitation factor | FS 5 |
| Accuracy class | 1 |

Connection data

| | |
|----------------------------------|--|
| Connection method | Screw connection |
| Conductor cross section flexible | 2x 2.5 mm ² ... 4 mm ² (Secondary terminals) |

Dimensions

Item dimensions

| | |
|--------|--------|
| Width | 30 mm |
| Height | 108 mm |
| Depth | 85 mm |

Item dimensions with alternative mounting

| | |
|-------|-------|
| Width | 85 mm |
|-------|-------|

PACT MCR-V2-6015-85-1000-1A-1 - Current transformer



2905886

<https://www.phoenixcontact.com/us/products/2905886>

| | |
|--------|--------|
| Height | 108 mm |
| Depth | 30 mm |

Copper rail

| | |
|--------|-------|
| Width | 60 mm |
| Height | 15 mm |

Copper rail 2

| | |
|--------|-------|
| Width | 50 mm |
| Height | 10 mm |

Copper rail 3

| | |
|--------|-------|
| Width | 40 mm |
| Height | 40 mm |

Circular conductor

| | |
|----------|-------|
| Diameter | 52 mm |
|----------|-------|

Material specifications

| | |
|------------------|------------------|
| Color | black (RAL 9005) |
| Housing material | PA 6.6 |

Environmental and real-life conditions

Ambient conditions

| | |
|---|----------------------------------|
| Ambient temperature (operation) | -25 °C ... 40 °C |
| Ambient temperature (storage/transport) | -25 °C ... 40 °C |
| Permissible humidity (operation) | Use only indoors, non-condensing |

Approvals

CE

| | |
|-------------|--------------|
| Certificate | CE-compliant |
|-------------|--------------|

UKCA

| | |
|-------------|----------------|
| Certificate | UKCA-compliant |
|-------------|----------------|

Standards and regulations

| | |
|-----------------------|----------|
| Standards/regulations | EN 61869 |
|-----------------------|----------|

PACT MCR-V2-6015-85-1000-1A-1 - Current transformer



2905886

<https://www.phoenixcontact.com/us/products/2905886>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

PACT MCR-V2-6015-85-1000-1A-1 - Current transformer



2905886

<https://www.phoenixcontact.com/us/products/2905886>

Accessories

PACT-FAST-MNT-W16-L65 - Mounting material

2276641

<https://www.phoenixcontact.com/us/products/2276641>



The transformer quick-action mechanism enables the lightning-fast mounting of PACT current transformers on the power rail. The installation can be completed easily by hand without the use of tools. Fixing pins: 65 mm, holding latches: 16 mm

PACT-FAST-MNT-W16-L40 - Mounting material

2276638

<https://www.phoenixcontact.com/us/products/2276638>



The transformer quick-action mechanism enables the lightning-fast mounting of PACT current transformers on the power rail. The installation can be completed easily by hand without the use of tools. Fixing pins: 40 mm, holding latches: 16 mm

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA

586 Fulling Mill Road

Middletown, PA 17057, United States

(+717) 944-1300

info@phoenixcon.com