

75 Ohm, 1 GHz, 85°C, ø5 mm, PVC jacket

G_03233

Properties

- Custom version of standard RG cable
- 75 Ohm characteristic Impedance



Construction			
Component	Material	Detail	Diameter
Centre conductor	Copper	Strand-07, RAL 9005 - bk	0.49 mm - 0.15 mm
Dielectric	PE (Polyethylene)		2.95 mm
Outer conductor	Copper	Braid, 95%	3.6 mm
Jacket	PVC (Polyvinyl chloride)	RAL 9005 - bk	5 mm +/- 0.15 mm

Electrical data	
Impedance	75 Ω +/- 3Ω
Operating frequency	≤ 1 GHz
Capacitance	67 pF/m
Velocity of signal propagation	66 %
Signal delay	5.03 ns/m
Screening effectiveness	39 dB at frequency 0.001 GHz ... 1GHz
Insulation resistance	100000000 MΩ*m
Inner conductor resistance	129.4 Ω/km
Operating Voltage (at sea level)	≤ 2.5 kVrms
Test voltage (50 Hz/1 min)	≤ 5 kVrms

Mechanical data	
Weight	approx. 39 g/m
Static bending radius	≥ 25 mm
Repeated bending radius	50 mm

Environmental data	
Operation temperature	-25 °C ... 85 °C
Installation temperature	-20 °C ... 60 °C
Fire characteristics	contains halogene

75 Ohm, 1 GHz, 85°C, Ø5 mm, PVC jacket

G_03233

Suitable connectors	
Cable group	U12

Ordering information		
Item number	Item description	Available as assembly only
22510135	G_03233	No

Power Matrix			
Calculation: typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]			
a coefficient typical =	0.4925	b coefficient typical =	0.035
fmax =	1	P at 1 GHz =	82
Frequency GHz	Nom. attenuation (dB/m)	Nom. attenuation (dB/ft)	CW power (W)
	sea level 25°C ambient temperature	sea level 25°C ambient temperature	sea level 40°C ambient temperature
0.10	0.159	0.049	259
0.20	0.227	0.069	183
0.30	0.280	0.085	150
0.40	0.325	0.099	130
0.60	0.402	0.123	106
0.80	0.469	0.143	92
1.00	0.527	0.161	82

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1072 / Date of publication: 08.08.2024 / uncontrolled copy