



PLUG CONFIG: MOLDED NEMA L6-20  
COLOR: BLACK

AWG: #12-3 YELLOW  
TYPE: SJEOOW, 300V  
AGENCY APPROVAL: UL & CSA CERTIFIED OR cUL  
(BOTH SIDE - PRIMARY & SECONDARY)

CONNECTOR CONFIG: MOLDED NEMA L6-20  
COLOR: BLACK

SPECIFICATION LABEL

**TECHNICAL**

AGENCY APPROVAL:	cULus
RATED SUPPLY VOLTAGE:	240 VAC
RATED CURRENT:	UP TO 20 AMPS
RESET TYPE:	AUTO/MANUAL
OPERATING FREQUENCY:	60 Hz
TYPE:	CLASS A
GROUND TRIP CURRENT:	5mA +/- 1mA
OVERLOAD CURRENT:	120 AMPS, 50% INDUCTIVE
INSULATION VOLTAGE:	1,500 VRMS - 1 MINUTE
ENDURANCE OPERATIONS:	3000 OPERATIONS
ENCLOSURE:	TYPE 4X, IP69, IP69K

MATERIAL NO.	PART NO.	"L" DIMENSION	"A" DIMENSION	POWER-UP
1301530157	24052-1MLDA	2 FT 9 IN	1 FT	AUTO
1301530158	24052-1MLDM	2 FT 9 IN	1 FT	MANUAL

<b>FUNCTIONAL SYMBOLS</b> $\nabla_A = 0$ $\nabla_C = 0$ $\nabla_P = 0$	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				
	DIMENSION UNITS	SCALE	CURRENT REV DESC: NEW SALES DRAWING CREATED		
	INCH	NTS	EC NO: 727155 DRWN: VBSUTHKARP 2022/11/03 CHK'D: DNGUYEN62 2022/12/16 APPR: WLEUNG 2022/12/29		
	GENERAL TOLERANCES (UNLESS SPECIFIED)				
ANGULAR TOL ± °		PRODUCT CUSTOMER DRAWING			
4 PLACES ±		DOCUMENT NUMBER			
3 PLACES ±		1301530157			
2 PLACES ±		DOC TYPE   DOC PART   REVISION			
1 PLACE ±		PSD   000   A			
0 PLACES ±		MATERIAL NUMBER   CUSTOMER   SHEET NUMBER			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	SEE TABLE   GENERAL MARKET   1 OF 1



INLINE GFCI 20A, 240V  
W/ MOLDED PLUG/CONNECTOR L6-20