

## Catalog No. 5340

**Description: 4 IN INSUL. LIQ.TIGHT CONN STRAIGH**

**UPC No 786210053400**

**Home > Cable Protection Systems > T&B Liquidtight Fittings > Liquid tight connectors**

4 Inch Straight Malleable Iron Insulated Liquidtight Connector



Representative Image

### Descriptors

Category	Liquid tight connectors
Type	Connectors-Straight
Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.

### Specifications

Material	Malleable Iron
Finish	Electro Zinc Plated/Chromate Coating

### Classifications

Brand Name	T&B Liquidtight Fittings
Standard	UL E23018, CSA

### Dimensions

Size	4 Inch
------	--------

### Compliance and Certifications

RoHS	RoHS3 Compliant
TSCA	TSCA Section 6(h) Compliant

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	4 inch
Model	Straight
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Thread
Thread type	NPT
Thread connection size	Other

ETIM	EC001180 Screw connection for protective metallic hose
One-piece	N
Material housing	Other
Approved in combination with protective conduit CSA	Y
Approved in combination with protective conduit UL	Y