


Specifications			Notes	Revision History																
Description	Value	Unit		Version	Description		Date	Approved												
Shape	Round		1) All dimensions are in mm unless otherwise noted 2) All parts meet RoHS  DB UNLIMITED	1	Released from Engineering		10/21/2013	J.S												
Resonant Frequency	450	(Hz)																		
Frequency Range	450 ~ 5,000	(Hz)																		
SPL @ 10cm	90	(dBA)																		
Impedance	16	(Ohm)																		
Cone Material	Paper																			
Nominal Power	0.5	(W)																		
Max Power	1	(W)																		
Mount Type	Flush Mount																			
Operating Temperature	-40 ~ +66	°C																		
Storage Temperature	-40 ~ +66	°C																		
Weight	49	(g)																		
				Dynamic Speaker		SP570416-1														
			<table border="1"> <tr> <th>Drawn by</th> <th>Date</th> <th>Checked by</th> <th>Date</th> <th>Approved by</th> <th>Date</th> </tr> <tr> <td>A.B.</td> <td>10/21/2013</td> <td>C.E.</td> <td>10/21/2013</td> <td>J.S</td> <td>10/21/2013</td> </tr> </table>		Drawn by	Date	Checked by	Date	Approved by	Date	A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013				
Drawn by	Date	Checked by	Date	Approved by	Date															
A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013															

Additional considerations can be found at www.dbunlimitedco.com/technical-articles.