






型号: KH-281511-TP


Rev.	ECN Number	Description	Date	Drawn	Checked	Approved

技术要求:


1. 材质: 不锈钢 SUS304, T=0.08±0.005.
2. 端子锡脚焊接面和接触面不可有毛边, 其他部位毛边最大0.03mm.
3. 扭曲: 4.5°/1000mm, 拱形 5mm/1000mm;
4. 标示有"▲"符号的为重点控制和检验尺寸;
5. 未标注之R MAX R0.13;
6. 电镀须满足4.8小时盐雾测试;
7. 寿命测试>2万次, 产品弹力要求在60gf~80gf之间
8. 镀底50 80u"min, 焊接区域镀金, 接触区域镀金3U"MIN



焊盘尺寸
尺寸公差 ±0.05



技术详询



GENERAL TOLERANCE		SCALE	DRAWN	DATE	DWG. NO.	REV.
XL ±0.50	XL ±2.0°	1:1	CHECK	DATE	681-0026B-1	A
X ±0.35	X ±1.0°	mm	APPROVE	DATE	PARTS NOT INTENDED USED	SHEET
.X ±0.25	.X ±1.0°	SIZE: A4			L2.8*W1.55*H1.1	1/1
.XX ±0.15	.XX ±0.5°					