


Hart lock complex environment locking devices

Product description


3-pole, 4-wire grounding
 30A, 3Ø 480V/AC
 NEMA L16-30




L1630PY



L1630CY



L1730CW



L1730RW

Hart lock 3Ø plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
30	480	L16-30	3Ø watertight	0.43-1.15" (10.9-29.2mm)	Y	□ L1630PW	□ L1630CW	•	•
			3Ø watertight	0.43-1.15" (10.9-29.2mm)	BK	□ L1630PWBK	□ L1630CWBK	•	•
			3Ø severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	□ L1630PY	□ L1630CY	•	•
			3Ø safety grip corrosion resistant	0.63-1.16" (15.9-29.4mm)	Y	□ CRL1630P	--		•


Hart lock 3Ø receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.		
30	480	L16-30	3Ø watertight	Y	□ L1630RW	•	•
			3Ø watertight	BK	□ L1630RWBK	•	•

Hart lock complex environment locking devices

Product description

3-pole, 4-wire grounding
 30A, 3Ø 600V/AC
 NEMA L17-30



Hart lock 3Ø plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
30	600	L17-30	3Ø watertight	0.43-1.15" (10.9-29.2mm)	Y	□ L1730PW	□ L1730CW	•	•
			3Ø watertight	0.43-1.15" (10.9-29.2mm)	BK	□ L1730PWBK	□ L1730CWBK	•	•
			3Ø severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	□ L1730PY	□ L1730CY	•	•

Hart lock 3Ø receptacles


Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.		
30	600	L17-30	3Ø watertight	Y	□ L1730RW	•	•
			3Ø watertight	BK	□ L1730RWBK	•	•

Dimensional information:
 D-34-35

Specification information:
 Watertight industrial plugs & connectors: D-38
 Watertight industrial receptacles: D-39
 Severe duty industrial plugs & connectors: D-40
 Corrosion resistant: D-41

Color information:

BK (Black), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-30

RoHS compliant - Page Q-30