


Part Number: 5306FE



Security & Sound, #18-8c, BC, Shielded, CMR

Product Description

Security & Sound Cable, Riser-CMR, 8-18 AWG stranded bare copper conductors with polyolefin insulation, Beldfoil® shield and PVC jacket with ripcord

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
18	7x26	BC - Bare Copper	8

Conductor Count: 8

Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.008 in

Color Chart

Number	Color
1	Black
2	Red
3	White
4	Green
5	Brown
6	Blue
7	Orange
8	Yellow

Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape w/Shorting Fold	Beldfoil®	100 %	TC - Tinned Copper	24	Solid mm

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.245 in	0.018 in	Yes

Electrical Characteristics

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
27 pF/ft	48.5 pF/ft

Construction and Dimensions

Print Legend:	NEW GENERATION(R) BY BELDEN 5306FE CMR 75C 8C18 SHIELDED (UL) E108998 OR C(UL) CMG----FT4 (2 FT., 7 DIGIT SEQUENTIAL) FEET
---------------	--

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
-----------------------	--------------------------

6.5 Ohm/1000ft	15.25 Ohm/1000ft
----------------	------------------

High Freq

Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. SRL (Structural Return Loss)	Min. TCL [dB]
	26 dB			
	26 dB	26 dB		
		26 dB		
			26 dB	
			26 dB	
26 dB/100m				
				26 dB
				26 dB
				26 dB
				26 dB

Current

Element	Max. Recommended Current [A]
10C Temperature Rise	Per conductor @ 25°C: 3.5 A

Voltage

UL Voltage Rating
300V RMS

Applicable Standards & Environmental Programs

CEC/C(UL) Specification:	CMG
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CPR Euroclass:	Eca
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Standards

NEC Articles:	800
NEC/(UL) Specification:	CMR

Flame Test

CSA Flammability:	FT4
UL Flammability:	UL1666 Riser

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Mechanical Characteristics

Operating Temp Range:	-20°C To +75°C
Bulk Cable Weight:	56 lbs/1000ft
Max Recommended Pulling Tension:	193.2 lbs
Min Bend Radius/Minor Axis:	2.5 in
Min Bend Radius/Installation:	26 in

Temperature Range

UL Temp Rating: 75°C

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 6306FE

History

Variants

Item #	Color
5306FE 0081000	Gray
5306FE 008500	Gray

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.