
1-881545-2 - ACTIVE

AMPMODU

TE Internal #: 1-881545-2 Novo, Open Top, 2 Position, 2.54 mm [.1 in] Centerline, Signal, -65 – 105 °C [-85 – 221 °F], Board-to-Board Jumpers & Shunts View on TE.com > **E T E connectivity**

Connectors > PCB Connectors > Board-to-Board Connectors > Board-to-Board Jumpers & Shunts



Shunt Type: Novo Shunt Style: Open Top Number of Positions: 2 Centerline (Pitch): 2.54 mm [.1 in]

Contact Current Rating (Max): **3**A

Features

Product Type Features

Connector System

Connector & Contact Terminates To

Configuration Features

Number of Positions

Board-to-Board

Printed Circuit Board

2

Electrical Characteristics

Termination Resistance	15 mΩ				
Body Features					
Handle	With				
Primary Product Color	Black				
Contact Features					
Contact Mating Area Plating Material Thickness	.762 μm[30 μin]				
Contact Mating Area Plating Material	Gold				
Contact Base Material	Phosphor Bronze				
Shunt Type	Novo				
Shunt Style	Open Top				
Contact Current Rating (Max)	3 A				
Mechanical Attachment					
Connector Mounting Type	Board Mount				

1-881545-2

Novo, Open Top, 2 Position, 2.54 mm [.1 in] Centerline, Signal, -65 – 105 °C [-85 – 221 °F], Board-to-Board Jumpers & Shunts



Housing Features

Housing Material	Thermoplastic					
Centerline (Pitch)	2.54 mm[.1 in]					
Dimensions						
Product Height	5.8 mm[.228 in]					
Usage Conditions						
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]					
Operation/Application						
Circuit Application	Signal					
Industry Standards						
UL Flammability Rating	UL 94V-0					
Packaging Features						
Jumper & Shunt Packaging	Loose Piece					
Packaging Quantity	14000					
Packaging Method	Bag					

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC	
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free	
Solder Process Capability	Not reviewed for solder process capability	

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products

1-881545-2

Novo, Open Top, 2 Position, 2.54 mm [.1 in] Centerline, Signal, -65 – 105 °C [-85 – 221 °F], Board-to-Board Jumpers & Shunts



will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Customers Also Bought



HEADER HE14 STRAIGHT 2X4 P	HOUSING HE13 HE14 COSI 3 P	PS0SXDSXA=C1110	T9SV1K15-12S
TE TE	- TE		
TE Part #5-104505-5 MTE PIN LP	TE Part #1969797-1 02P UMNL HDR ASSY R/A, SCKT V0 GW	TE Part #2344655-6 PCB ANT, MHF 4, 100mm, Wi-Fi TRIPLE BAND	TE Part #1337769-2 500HM COAX BNC STR PLUG STR P



Documents

Product Drawings

C For support call+1 800 522 6752

1-881545-2

Novo, Open Top, 2 Position, 2.54 mm [.1 in] Centerline, Signal, -65 – 105 °C [-85 – 221 °F], Board-to-Board Jumpers & Shunts



AMP SHUNT ASS'Y

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_1-881545-2_K.2d_dxf.zip

English

Customer View Model

ENG_CVM_1-881545-2_K.3d_igs.zip

English

Customer View Model

ENG_CVM_1-881545-2_K.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Agency Approvals Agency Approval Document

English