


NOTE:

1. Rating: DC 16V 0.5A.
2. Dielectric withstanding : AC 500V for 1minute.
3. Contact resistance : 200mΩ Max.
4. Insulation Resistance : 50mΩ Min.
5. Operating Force: 30gf±10gf.
6. Mechanical Life: 50000 CYCLES.



CIRCUIT DIAGRAM

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑥	Terminal	—	2	Brass	Plating silver	—
⑤	Bottom	—	1	PC	transparent	—
④	Spring	—	1	SUS	Natural	—
③	Contact	—	1	Beryllium copper	—	—
②	Base	—	1	PA46	Black	—
①	Knob	—	1	POM	Black	—

APPROVALS		DATE		HRO 韓榮® ELECTRONICS CO.,LTD			
DRAWN	LIUCAN	2021.05.26		TITLE:	DETECTOR SWITCHS		
CHECKED				PART NO.	K5-1678DA-01		
APPROVALS				TOLERANCES ARE	ANGLE	UNIT: mm	
		30~以上	±0.30	±2°	DRAWING NO.	SCALE: 1:1	
		10~30	±0.20				
		5~10	±0.15				
		~ 5	±0.10			PROJ:	
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	SHEET 1 OF 1

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			