

Shrink sleeve - WMS-2 HF 4,8 (EX9)R GN - 0804496

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Shrink sleeve, Roll, green, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK W, Cut, Mounting type: slide on, Cable diameter: 2.4-4.8 mm, Lettering field: continuous x 9 mm

The figure shows a similar product

Why buy this product

- The sleeves remain flexible after shrinking
- The conductor to be marked is simply threaded through the sleeve and fixed by shrinking the sleeve
- The shrink sleeves provide additional electrical insulation and mechanical protection for the conductors
- The conductor to be marked is simply threaded through the sleeve and fixed by shrinking the sleeve
- Up to four markers per sleeve are separated by perforations
- The shrink sleeves provide additional electrical insulation and mechanical protection for the conductors
- Up to four markers per sleeve are separated by perforations

Key Commercial Data

| | |
|----------------------|---|
| Packing unit | 1 |
| GTIN |  4 055626 381176 |
| GTIN | 4055626381176 |
| Custom tariff number | 39173200 |

Technical data

Standards and Regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| | DIN EN 61010-1 (VDE 0411-1) |
| | DIN EN 61010-1 (VDE 0411-1) |
| | DIN EN 61010-1 (VDE 0411-1) |