

Part Number : 2162901011

Product Description : Standard .093" Femaleto-Standard .093" Female Off-the-Shelf (OTS) Cable Assembly, Single Row, 150.00mm Length, Tin (Sn) Plating, 1 Circuit, Natural Status : Active

Series Number : 216290 Product Category : Power and Signal Cable Assemblies

Documents & Resources

Drawings Drawing 2162901011_sd.pdf

3D Models and Design Files

3D Model 2162901011_stp.zip

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|----------------------------------------------------|
| China RoHS | © |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

| Status | Active |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Category | Power and Signal Cable Assemblies |
| Series | 216290 |
| Description | Standard .093" Female-to-Standard .093" Female Off-the-Shelf (OTS) Cable Assembly, Single Row, 150.00mm Length, Tin (Sn) Plating, 1 Circuit, Natural |
| Application | Power, Wire-to-Wire |
| Assembly Configuration | Dual Ended Connectors |
| Connector to Connector | Standard 093"-to-Standard 093" |
| Product Family | Standard .093" Pin and Socket Connectors |
| Product Name | Standard .093" |
| Туре | Discrete Wire Assembly |
| UPC | 193264734696 |

Electrical

| Current - Maximum per Contact | 12.0A |
|-------------------------------|------------------|
| Voltage - Maximum | 600V AC (RMS)/DC |

Physical

| Cable Length | 150.00mm |
|--------------------------------|---------------|
| Circuits (Loaded) | 1 |
| Circuits (maximum) | 1 |
| Color - Resin | Natural |
| Gender | Female-Female |
| Lock to Mating Part | Yes |
| Material - Metal | Brass |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Material - Resin | Nylon |
| Net Weight | 8.271/g |

| Number of Rows | 1 |
|-----------------------------|----------------------|
| Overmolded | No |
| Packaging Type | Bag |
| Pitch - Mating Interface | 6.70mm |
| Plating min - Mating | 0.508µm |
| Plating min - Termination | 0.508µm |
| Single Ended | No |
| Termination Interface Style | Crimp or Compression |
| Wire/Cable Type | UL 1015 |
| Wire Insulation Diameter | 1.65-4.06mm |
| Wire Size (AWG) | 14 |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|--------------------------------------------------------------------------------------------------------------------------------|-----------------|
| 2.36mm Diameter Standard .093" Pin and Socket Plug Housing with Positive Latch, UL 94V-0, 1 Circuit | <u>19092016</u> |
| 2.36mm Diameter Standard .093" Pin and Socket Plug Housing with Positive Latch, UL 94V-0, with Panel Mount, 1 Circuit | <u>19092017</u> |
| 2.36mm Diameter Standard .093" Pin and Socket Plug Housing with Positive Latch, UL 94V-2, with Panel Mount, 1 Circuit | <u>19092018</u> |

This document was generated on Sep 17, 2024