



## 414U FEMALE BODY BSP PARALLEL

	DN (mm)	Flow Rate (l/min)	C	E (mm)	F (mm)	ØG (mm)	L (mm)	 (kg)
9414U06 13	5,5	1250	G1/4	12,0	17,0	31,5	66,5	0,070
9414U06 17	5,5	1250	G3/8	12,0	22,0	31,5	72,0	0,085
9414U06 21	5,5	1250	G1/2	15,0	27,0	31,5	78,0	0,115
9414U08 13	8,0	2250	G1/4	12,0	22,0	36,5	75,0	0,127
9414U08 17	8,0	2250	G3/8	12,0	22,0	36,5	75,0	0,144
9414U08 21	8,0	2250	G1/2	15,0	27,0	36,5	80,0	0,138



**414U**  
**FEMALE BODY BSP PARALLEL**

**414U**

<b>maximum working pressure</b>	<b>bar</b> 16	<b>MPa</b> 1,6	<b>psi</b> 232
<b>working temperature</b>	<b>°C</b> <b>(Celsius)</b> From -20 to 60	<b>F</b> <b>(Fahrenheit)</b> From -4 to 140	<b>K</b> <b>(Kelvin)</b> From 253 to 333
<b>ball</b>	stainless steel		
<b>body</b>	engineering grade polymer		
<b>sub-base</b>	nickel-plated brass		
<b>'O'-rings</b>	nitrile		
<b>spring</b>	stainless steel		