

BAC05S05DC

In Production Recommended New RoHS

Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Consumer equipment, Industrial	
	Equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
Specific	the performance, functions, quality,	
Applications	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	
Recommended	lealated AC DC nowar aurphy	
Applications	Isolated AC-DC power supply	



http://www.murata.com/en/products/productdetail?partno=BAC05S05DC

Features

5V 1A, Isolated 5W Regulated Single Output 4.25kVAC, AC-DC Converters, 85-264VAC/120-370VDC Input

Appearance & Shape



1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.







BAC05S05DC

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of BAC05S05DC from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=BAC05S05DC

Specifications

Output power (W)Max	5W
Vin (VAC)	85Vac to 264Vac
Vin (VAC)typ	230Vac
Vin (VDC)	120Vdc to 370Vdc
Vout(V)	5V
Vout(V)typ	5V
LineRegulation (%)	-0.5% to 0.5%
LoadRegulation (%)	-1% to 1%
Isolation Voltage (V)	4700V
Efficiency (%)	75.5%
Size(mm)W	25.4mm
Size(mm)L	25.4mm
Size(mm)T	16.3mm
Operatingtemperature(degC)	-40°C to 85°C
Outputs (#)	1
lout(A)Max	1A
Package	DIP
Productseries	BAC05

	The BAC05 series delivers an
	output power of 5 watts from -
	40°C to 55°C, operating up to
	85°C with derating, from AC or
	DC input voltages. The BAC05
	series small footprint is EMC
	class B compliant without the
	need of any external
	components. The BAC05
Product Series Features	series is suited to medical
Floduct Selles Features	applications with 1 MOPP and
	2 MOOP.
	With high efficiency at low
	loads and low no load power
	consumption, the BAC05
	supports standby mode
	operation for applications in
	industrial, medical, automation,
	IOT as well as household and
	home automation.
	UL62368-1, EN62368-1,
Safety Approval	IEC61558-1, IEC61558-2-16,
	ANSI/AAMI ES60601-1

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

