

Wire

Kynar



Specifications

This specifications is for wire per UL style 1423, solid silver-plated oxygen free copper

No voltage ratings for any size

*AWG = American wire gauge

*AWG	30
Conductor Material	Silver plated oxygen free, high conductivity copper per ASTM-B 170 grade
Plating Material	Minimum 40 microns per ASTM-B-298
Conductor Diameter	0.25
Conductor Elongation	20% before insulation
Insulation Material	Kynar 460
Insulation Average Wall Thickness	0.15
Total Diameter	0.5
Conductor Resistance ohms / 1,000 feet at 20°C	106
Spark Test	2,000 V ac rms
Maximum Service Temperature (°C)	105

Test Requirements :

100% per UL style 1,423 and subject 758

Dielectric : 2,000 V ac rms spark test

DCR : 106 ohms / 100 feet maximum at 20°C

Part Number Table

Description	Part Number
Wire, Kynar, 30 AWG, Black, 100 m	100-30BK

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.