



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Documents**

Application note

AN001 "Calibration Services"

**Material and plating**

**Connector parts**

- Center and outer contact
- Gauge block coupling nut
- Gauge block body

**Material**

- Stainless steel
- Stainless steel
- Stainless steel

**Plating**

- N/A
- Passivated
- N/A

**Mechanical data**

- Gauge block nominal gauge 5.28 mm
- Gauge range 5.28 mm ± 0.5 mm
- Scale gradation 1 µm
- Limit of measurement error<sup>1,2</sup> ≤ 10 µm
- Typical measurement error<sup>1,2</sup> ≤ 6 µm
- Measuring force 1.5 N

<sup>1</sup> When zeroed with gauge block  
<sup>2</sup> 5.24 mm to 5.40 mm

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/09.14/6.2

**Declaration of calibration options**

**Factory Calibration**

Standard delivery for this gauge includes a Factory Calibration. The Calibration Certificate issued reports individual mechanical calibration results, traceable to national / international standards.

**Accredited Calibration**

Not available.

*For further, more detailed information see application note AN001 on the Rosenberger homepage.*

**Calibration interval**

Recommendation 12 months

**Packing**

Standard 1 pce in box  
Weight 206.8 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

| Draft  | Date     | Approved     | Date     | Rev. | Engineering change number                           | Name      | Date          |
|--|----------|--------------|----------|------|---|-----------|---------------|
| Herbert Babinger   | 02.03.05 | Martin Moder | 08.03.19 | h00  | 19-0388   | S. Schmid | 06.03.19      |
| Rosenberger Hochfrequenztechnik GmbH & Co. KG<br>P.O.Box 1260 D-84526 Tittmoning Germany<br>www.rosenberger.de |          |              |          |      | Tel. : +49 8684 18-0<br>Email : info@rosenberger.de |           | Page<br>2 / 2 |