


**EM3526 Series
EuroMag Terminal Blocks**

Closed and Open Header (Mates with EM3516 Series); 7.62 Centers

SPECIFICATIONS


- Rating:** 15A, 300V
- Center Spacing:** 0.30" (7.62mm)
- Housing Material:** UL rated 94V0 Thermoplastic
- Contact Material:** Brass Tin-Plated
- Operating Temperature:** 105°C (221°F) max., -40°C (-40°F) min.
- Recommended PCB Hole Diameters:** 0.055" (1.40mm)
- Construction:** Mold-to-Length
- Agency Information:** File E62622; CE Certified



Dimensions - mm (in)

Poles	Open L (mm)	Closed L (mm)
2	13.44	15.24
3	21.06	22.86
4	28.68	30.48
5	36.60	38.10
6	43.92	45.72
7	51.54	53.34
8	59.16	60.96
9	66.78	68.58
10	74.40	76.20
11	82.02	83.82
12	89.64	91.44

To convert to inches, divide by 25.4



Part Numbering System

Series	# of Poles	Orientation	Side Base	Mating Plug: EM3516 pg. 99
EM3526	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
	02 to 24	H - horizontal V - vertical	O - open C - closed	

Terminal Blocks: Single Row
EuroMag Series Plug & Header
Edge Connectors, One-Sided Boards
Compliance References

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Eaton:

[EM352604VO](#) [EM352610HC](#) [EM352611VO](#) [EM352612HC](#) [EM352607VC](#) [EM352608HO](#) [EM352606HO](#)
[EM352608VO](#) [EM352602VC](#) [EM352604VC](#) [EM352611HC](#) [EM352609HO](#) [EM352607VO](#) [EM352607HO](#)
[EM352610VC](#) [EM352605VC](#) [EM352606HC](#) [EM352609HC](#) [EM352602VO](#) [EM352611HO](#) [EM352604HO](#)
[EM352605HO](#) [EM352607HC](#) [EM352603VO](#) [EM352604HC](#) [EM352612VO](#) [EM352609VO](#) [EM352602HC](#)
[EM352608HC](#) [EM352610VO](#) [EM352603VC](#) [EM352611VC](#) [EM352606VC](#) [EM352612VC](#) [EM352612HO](#)
[EM352609VC](#) [EM352605HC](#) [EM352608VC](#) [EM352602HO](#) [EM352606VO](#) [EM352603HC](#) [EM352603HO](#)
[EM352610HO](#) [EM352605VO](#)