

## General Information

Extended Product Type:	M35/26.FF
Product ID:	1SNA115140R2300
EAN:	3472591151404
Catalog Description:	M35/26.FF
Long Description:	M35/26.FF Power Terminal Blocks - Feed-through - Grey, 25mm <sup>2</sup> RatedCrossSection, 26mm Spacing G32, TH 35-7.5, TH 35-15 Rail

## Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Power Terminal Blocks

## Ordering

EAN:	3472591151404
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85369010

## Dimensions

Product Net Width:	26.0 mm
Product Net Height:	66.0 mm
Product Net Depth:	44.0 mm
Product Net Weight:	64.00 g

## Container Information

Package Level 1 Units:	10 piece
Package Level 1 Width:	120 mm
Package Level 1 Height:	57 mm
Package Level 1 Length:	130 mm
Package Level 1 Gross Weight:	0.64000 kg
Package Level 1 EAN:	3472591151404
Package Level 2 Units:	300 piece
Package Level 2 Width:	300 mm
Package Level 2 Height:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Gross Weight:	19.7 kg
Package Level 3 Units:	7200 piece
Product Packing Type:	Box

## Environmental

Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007-01-01

## Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Connecting Capacity-Main Circuit UL/CSA:	Stud / Rigid 1x 10 ... 2 AWG

## Additional Information

Ambient Temperature:	-5 ... +40 °C
Color:	Grey
Connecting Capacity-Main Circuit:	Stud / Flexible 1x 2.5 ... 25 mm <sup>2</sup> Stud / Rigid 1x 2.5 ... 50 mm <sup>2</sup>
Connection Type:	Stud
Function:	Feed-through
IIT Publishing Status:	Level 0 - Information enabled
Insulation Material:	Polyamide
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Levels:	1
Pollution Degree:	3
Product Main Type:	M35/26.FF
Product Name:	Terminal block
Rated Cross-Section:	25 mm <sup>2</sup>

<b>Rated Current (<math>I_n</math>):</b>	Main Circuit 101 A
<b>Rated Short-time Withstand Current (<math>I_{cw}</math>):</b>	for 1.0s 8000 A
<b>Rated Voltage (<math>U_r</math>):</b>	1000 V
<b>Spacing:</b>	26 mm

#### Certificates and Declarations (Document Number)

<b>CSA Certificate:</b>	TBD-from cat 2010
<b>cUL Certificate:</b>	1SND165000A0203
<b>Declaration of Conformity - CE:</b>	1SND225008C1006
<b>EAC Certificate:</b>	1SND161009A1100
<b>GOST Certificate:</b>	1SND161005A1104
<b>RoHS Information:</b>	1SND230022F0201

#### Classifications

<b>ETIM 4.0:</b>	EC000897 - Feed-through terminal block
<b>ETIM 5.0:</b>	EC000897 - Feed-through terminal block
<b>Object Classification Code:</b>	X

