

# Pin strip - PST 1,3/16-5,0 L15,5 - 1845959

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Pin strip, nominal current: 12 A, number of positions: 16, pitch: 5 mm, color: black, contact surface: Tin, The maximum current depends on the plug used. The lower of the two current values apply for plug and pin strip. The pin strip is made of highly temperature resistant plastic and is thus suitable for the reflow process.

┥┥┥┥

The figure shows a 6-position version

### Your advantages

- Suitable for wave and reflow soldering processes
- ☑ Optimum pin geometry for all COMBICON pin strip connectors



# Key Commercial Data

Packing unit	50 pc
GTIN	4 046356 980081
GTIN	4046356980081

### Technical data

#### Dimensions

Pitch	5 mm
Dimension a	75 mm
Height	9.5 mm
Length of the solder pin	3.5 mm
Pin dimensions	ø 1.3 mm

### General

Range of articles	PST 1,3/V
Rated voltage (III/3)	250 V
Connection in acc. with standard	EN-VDE
Nominal current I <sub>N</sub>	12 A
Color	black
Number of positions	16



# Pin strip - PST 1,3/16-5,0 L15,5 - 1845959

# Technical data

### Standards and Regulations

Connection in acc. with standard	EN-VDE	
Environmental Product Compliance		
China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

## Approvals

#### Approvals

Approvals

EAC

#### Ex Approvals

### Approval details

EAC	B.01742
-----	---------

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1845959