ER4003-000 🗸 ACTIVE

HX-CT

TE Internal #: ER4003-000 Continuous, Low Fire Hazard, 2:1 Shrink Ratio, Black, 2.4mm [.094in] Expanded Inside Diameter, HX-CT, Printable Tubing View on TE.com >



Identification & Labeling > Printable Tubing > Continuous Tube, Low Fire Hazard HX-CT



Printable Tubing Type: Continuous
Printable Tubing Grade: Low Fire Hazard
Shrink Ratio: 2:1
Primary Product Color: Black
Expanded Inside Diameter (Min): 2.4 mm [.094 in]

All Continuous Tube, Low Fire Hazard HX-CT (27)

Features

Product Type Features

Printable Tubing Type

Printable Tubing Grade

Continuous

Low Fire Hazard

Body Features

Shrink Ratio	2:1
Primary Product Color	Black
Dimensions	
Expanded Inside Diameter (Min)	2.4 mm[.094 in]
Recovered Inside Diameter (Max)	1.19 mm[.047 in]
Compatible Cable Diameter Range	1.2 – 1.9 mm[.05 – .075 in]
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
Printer/Label Features	
Printer Technology	Thermal Transfer
Packaging Features	
Packaging Quantity	50

ER4003-000

Continuous, Low Fire Hazard, 2:1 Shrink Ratio, Black, 2.4mm [.094in] Expanded Inside Diameter, HX-CT, Printable Tubing



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



ER4003-000

Continuous, Low Fire Hazard, 2:1 Shrink Ratio, Black, 2.4mm [.094in] Expanded Inside Diameter, HX-CT, Printable Tubing







Also in the Series HX-CT



Documents

Product Drawings HX-CT-50M-2.4-OUT-0

English

Datasheets & Catalog Pages Printable Continuous Tubing English HX-CT, Low Fire Hazard Continuous Heat Shrink Identification Tube

English

Cable Identification Product Shelf Life

English

Product Specifications Product Specification

English

Instruction Sheets

C For support call+1 800 522 6752

ER4003-000

Continuous, Low Fire Hazard, 2:1 Shrink Ratio, Black, 2.4mm [.094in] Expanded Inside Diameter, HX-CT, Printable Tubing



Instruction Sheet (non U.S.)

English