

# EEM-EM375 - Measuring device



2908581

<https://www.phoenixcontact.com/us/products/2908581>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

3-phase energy meter for active power measurement with current transformer measurement  
1 A/5 A in grids of up to 500 V, with S0 output, Ethernet interface, certified in accordance with the  
MID directive



## Commercial data

Item number	2908581
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C446
Product key	CK4C11
Catalog page	Page 205 (C-5-2019)
GTIN	4055626338248
Weight per piece (including packing)	450 g
Weight per piece (excluding packing)	459.7 g
Customs tariff number	90283019
Country of origin	IT

## Technical data

### Product properties

Product type	Energy meter
Data management status	
Article revision	04
Insulation characteristics	
Protection class	II (EN 50470-1)
Insulation characteristics	
Pollution degree	2

### Electrical properties

Electric strength	6 kV
	4 kV (EN 50470-3, 7.2)
Supply	
Supply voltage range	Supply from the measuring circuit

### Input data

Measurement	
Input voltage range	3x 184 V ... 288 V (320 V ... 500 V)
Input current range	up to transformer ratio 10000
Power consumption	3.5 VA (1 W)
Frequency range	45 Hz ... 65 Hz
Start current $I_{st}$	0.002 A
Minimal current $I_{min}$	0.01 A
Maximum current $I_{max}$	6 A
Transient current $I_{tr}$	0.05 A
Nominal current $I_{ref}$	1 A
Secondary rated current $I_{sn}$	1 A
	5 A
Current transformer ratio	1 ... 10000 (max. 10000/1 or 50000/5)
Current transformer load	1.5 mΩ
Energy (EN 50470-3)	Class B
Real energy (IEC 62053-21)	Class 1
Reactive power (IEC 62053-23)	Class 2

### Output data

S0 output	
Output description	Passive opto-isolated
Maximum switching voltage	27 V DC

# EEM-EM375 - Measuring device



2908581

<https://www.phoenixcontact.com/us/products/2908581>

Max. switching current	27 mA
Pulse time	50 ms ±2 ms
Pause time	30 ms ±2 ms
Pulse LED	10000 imp/kWh
Meter constant	100 imp/kWh, kVAh, kvarh 1000 imp/kWh, kVAh, kvarh (CT 1 ... 4) 200 imp/kWh, kVAh, kvarh (CT 5 ... 24) 40 imp/kWh, kVAh, kvarh (CT 25 ... 124) 8 imp/kWh, kVAh, kvarh (CT 125 ... 624) 1 imp/kWh, kVAh, kvarh (CT 625 ... 3124) 0.1 imp/kWh, kVAh, kvarh (CT 3125 ... 10000)

## Connection data

### Measurement connection

Connection method	Screw connection
Conductor cross section rigid	1.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>
Conductor cross section flexible	1.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>
Conductor cross section AWG	16 ... 10 (rigid/flexible)
Tightening torque	1.5 Nm

### Other connections

Connection method	Screw connection
Conductor cross section rigid	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section flexible	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section AWG	26 ... 16 (rigid/flexible)
Tightening torque	0.5 Nm

## Interfaces

### Communication:

Communication protocol	Modbus/TCP HTTP NTP DHCP FTP
Communication standard	IEEE 802.3
Connection method	RJ45
Transmission speed range	10 Mbps ... 100 Mbps

## Dimensions

Width	72 mm
Height	90 mm
Depth	67 mm

## Environmental and real-life conditions

# EEM-EM375 - Measuring device



2908581

<https://www.phoenixcontact.com/us/products/2908581>

## Ambient conditions

Degree of protection (Front)	IP51 (Front)
Degree of protection (Connections)	IP20 (Connections)
Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 75 °C
Max. permissible relative humidity (operation)	80 %

## Approvals

### CE

Certificate	CE-compliant
-------------	--------------

### MID

Identification	MID-compliant
----------------	---------------

## Standards and regulations

Standards/specifications	EN 50470-1
	EN 50470-3

## Mounting

Thread type	()
-------------	----

# EEM-EM375 - Measuring device


2908581

<https://www.phoenixcontact.com/us/products/2908581>



## Drawings

Connection diagram



# EEM-EM375 - Measuring device



2908581

<https://www.phoenixcontact.com/us/products/2908581>

## Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2908581>



**EAC**

Approval ID: RU \*-DE.A\*30.B.01628

**MID**

Approval ID: No. 306/MID

# EEM-EM375 - Measuring device



2908581

<https://www.phoenixcontact.com/us/products/2908581>

## Classifications

### ECLASS

ECLASS-11.0	27142330
ECLASS-12.0	27142330
ECLASS-13.0	27142330

### ETIM

ETIM 9.0	EC002301
----------	----------

### UNSPSC

UNSPSC 21.0	41113600
-------------	----------

# EEM-EM375 - Measuring device



2908581

<https://www.phoenixcontact.com/us/products/2908581>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)